COG-702^Q&As

IBM Cognos TM1 10.1 Developer

Pass IBM COG-702 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/COG-702.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

🌟 **Instant Download** After Purchase

🌟 **100% Money Back** Guarantee

🌟 **365 Days** Free Update

🌟 **800,000+** Satisfied Customers

QUESTION 1

You want to export only user-entered non-zero numeric values from a cube. Which three view manipulation functions are required? (Choose three.)

A. ViewExtractSkipZeroesSet (exclude zero/null values in export)

B. ViewExtractSkipRuleValuesSet (exclude rule calculated values in export)

C. ViewExtractSkipStringSet (exclude string values in export)

D. ViewExtractSkipCalcsSet (exclude consolidated values in export)

E. ViewExtractSkipLevelZero (exclude leaf level values in export)

Correct Answer: ABD

QUESTION 2

Which action must you take before the TM1 cubes can be used in IBM Cognos B1?

A. Define levels for all dimensions in TM1.

B. Define Measure dimensions for all cubes in TM1.

C. Define security for all elements in TM1.

D. Create an administrator account for IBM Cognos B1 to use.

Correct Answer: B

QUESTION 3

Click the Exhibit button.

Referring to the exhibit, a rule is written where the sales_amt is equal to units multiplied by avg selling price What does the cube view tell you about the rule calculation?

A. The rule is missing a Skipcheck statement.

B. The rule is overfed.

C. The rule is underfed

D. The ruled calculation is missing a feeder.

Correct Answer: C

QUESTION 4

Which statement is true for TM1 dimensions?

A. TM1 can have dimension hierarchies with only one roll-up/consolidation structure per dimension.

B. All dimension attributes must be unique across dimension elements.

C. Dimension aliases must be unique across dimension elements.

D. Dimension attributes can be either type numeric, type subset, or type string/text.

Correct Answer: C

QUESTION 5

If vOriginalDate = July 27, and you require vNewDate = Jul2012, which syntax is appropriate to complete this task?

A. vNewDate=SUBST(vOriginalDate,3,3) | \\'2012\\';

B. vNewDate=SUBST(vOriginalDate,3,3) and \\'2012\\';

C. vOriginalDate=SUBST(vNewDate,3,3) and \\'2012\\';

D. vNewDate=SUBST(vOriginalDate,3,3) + \\'2012\\';

Correct Answer: A

[COG-702 Practice Test](#)   [COG-702 Study Guide](#)   [COG-702 Braindumps](#)

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.passapply.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: