



E20-351^{Q&As}

Storage Attached Network (SAN) Specialist Exam

Pass EMC E20-351 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/e20-351.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Your customer has a multi-layer fabric that is experiencing an environmental-wide slowdown in performance. The customer has hosts in one layer, and all storage in another. What is the best possible measure that can be implemented in the customers environment to alleviate this performance issue?

- A. Add additional cache to the storage array/s
- B. Add additional disks/storage
- C. Add additional HBAs to the servers
- D. Add additional interswitch links between the switches

Correct Answer: D

QUESTION 2

Click the Exhibit button. Which type of port would these links register as? ****Exhibit Missing****

- A. E_Port
- B. F_Port
- C. FL_Port
- D. G_Port

Correct Answer: A

QUESTION 3

A data center contains the equipment and software required for a three-tier web application: a public-facing web server and an Oracle database, both of which are connected to storage via a SAN. The management server that hosts all required management applications is not connected to the SAN. What is a security best practice that should be established?

- A. Allow all support personnel to log in to the application they are responsible for with fullaccess for faster problem resolution
- B. Connect the management server to the SAN to allow for faster problem resolution
- C. Only log the network traffic of the public-facing web server
- D. Use encrypted or key exchange protocols to ensure that passwords cannot be sniffed

Correct Answer: D

QUESTION 4



What describes the non-blocking architecture deployed in M-Series switches?

- A. Allows data movement across the bus through CMM and finally to MPC for delivery
- B. Allows fencing of memory partitions into bit-buckets for data delivery
- C. Allows frames to be sent to destination ports based on the receiving ports availability
- D. Allows memory segmentation across the s/bar platform permitting data redirection basedon ASIC availability

Correct Answer: C

QUESTION 5

What is the default initial setup user that installs and sets up the Symmetrix Management Console environment?

- A. eccadmin
- B. emcadmin
- C. smc
- D. smcadmin

Correct Answer: C

[E20-351 Practice Test](#)

[E20-351 Study Guide](#)

[E20-351 Braindumps](#)