

E20-594^{Q&As}

Backup and Recovery - Avamar Specialist Exam for Implementation Engineers

Pass EMC E20-594 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/e20-594.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by EMC Official Exam Center

Instant Download After Purchase

- 100% Money Back Guarantee
- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

You have been asked to deploy a Dell EMC Avamar Virtual Edition (AVE) at a local field office. The requirement is to back up the Windows file server and the file system of nine Windows desktop computers. From historical data you know that daily changed data never exceeds 7 GBs.

What is the smallest AVE that should be deployed?

A. 0.5 TB

B. 1 TB

C. 2 TB

D. 4 TB

Correct Answer: A

Reference: https://www.emc.com/collateral/TechnicalDocument/docu89907.pdf

QUESTION 2

Which hash is an identifier for the entire point-in-time backup in a Dell EMC Avamar server?

A. Stripe

- B. Composite
- C. Atomic
- D. Root

Correct Answer: D

Reference: https://www.dell.com/community/Avamar/How-data-is-written-to-avamar-nodes/td-p/6860229

QUESTION 3

Refer to the exhibit.



Get Data Domain System Information Get Data Domain system information initiated... Failed to get Data Domain system information. Event Information: Event Code: 30941 Category: APPLICATION Severity: PROCESS Summary: Failed to connect to Data Domain system View Details Close

You are adding a new Data Domain to a Dell EMC Avamar server. After entering the required information, you go to validate your setting by clicking on "Get Stream Count" and the following message appears.

Based on the exhibit, what is a cause for receiving this error message?

- A. Wrong Data Domain hostname
- B. Wrong SNMP name
- C. Wrong DDboost user password
- D. Wrong Version of DDOS

Correct Answer: B

QUESTION 4

After replacement of the utility node, a Dell EMC Avamar server fails to start up completely. All the hardware appears to be functioning correctly.

What is a cause for this issue?

- A. Newly replaced utility node has faulted and must be replaced again
- B. NICs from the old utility node were not transplanted into the new utility node
- C. New license was not generated and installed



D. Server was not rolled back to a previous checkpoint when failing to start

Correct Answer: A

QUESTION 5

Which port does EMC Avamar use to access the Management Console database for reporting?

A. 7778

B. 28002

C. 29000

D. 5555

Correct Answer: D

E20-594 PDF Dumps

E20-594 Exam Questions

E20-594 Braindumps