



E20-616^{Q&As}

Symmetrix Installation and Troubleshooting Specialist

Pass EMC E20-616 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/e20-616.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the vault hyper size in GB for configuring a new VMAX 40K?

- A. 9
- B. 5
- C. 4.5
- D. 0.5

Correct Answer: A

QUESTION 2

Starting with which microcode level requires you to have a secure logon ID in order to operate the Service Processor?

- A. 5772
- B. 5876
- C. 5875
- D. 5773

Correct Answer: A

QUESTION 3

SPS 2A in Storage Bay 1A has a life of 300 seconds. How many power failures can it withstand?

- A. 1
- B. 2
- C. 5
- D. 4

Correct Answer: A

QUESTION 4

You are configuring SRDF on a single bay VMAX 10K. Which Director slices can you select for the Fiber Channel RF links while maintaining redundancy?

- A. 1H, 2H



B. 7H, 8H

C. 7G, 8G

D. 1H, 1G

Correct Answer: A

QUESTION 5

On a VMAX 10K, what is a Power Vault requirement?

A. 20 vault devices per engine

B. 32 vault devices per engine

C. Vault devices are configured on the first five drives of all DAEs.

D. Five vault drives per DA slice

Correct Answer: B

[Latest E20-616 Dumps](#)

[E20-616 Practice Test](#)

[E20-616 Braindumps](#)