HC-711-ENU^{Q&As}

HCNA Huawei Certified Network Associate - Constructing Basic Security Network (HCNA-CBSN) - ENU

Pass Huawei HC-711-ENU Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/hc-711-enu.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

About L2TP VPN configuration statement is correct: (Choose three)

A. The LNS L2TP client must configure the IP address of the virtual interface template,and the virtual interface template need to join the security domain

B. Firewall policies in order to ensure the normal dial-up users log on,you must configure the firewall to receive L2TP tunnel packets security zone where the physical interface between the regions and the Local

C. Dial-up users need access to internal network resources, you must configure the firewall policy template region corresponding virtual interface and internal security network located between areas where security

D. If a virtual template interface is added to a safe area,you can directly delete the security zone.

Correct Answer: ABC

QUESTION 2

When the port is configured to allow certain vlan trunk through, trunk belongs to these vlan.

A. True

B. False

Correct Answer: A

QUESTION 3

Which TSM system mainly consists of the following components? (Choose three)

A. SM management server

B. SC control server

C. Admission Control

D. Anti -virus server

Correct Answer: ABC

QUESTION 4

SVN provides the following IP address allocation which way? (Choose three)

A. DHCP allocation

B. IP address pool(randomly assigned)

C. IP address pool(user account with an IP address binding)

D. Virtual IP address allocation

Correct Answer: ABC

QUESTION 5

Similar anti- mask and subnet mask format, but the value has different meanings: 1 indicates that the corresponding IP address bits need to compare, 0 indicates that the corresponding IP address bits ignored comparison.

A. True

B. False

Correct Answer: B

[HC-711-ENU PDF Dumps](link)   [HC-711-ENU Practice Test](link)   [HC-711-ENU Exam Questions](link)