



HH0-450^{Q&As}

Hitachi Data Systems Storage Architect-Hitachi NAS Platform

Pass Hitachi HH0-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hh0-450.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

The administrator of a production Hitachi NAS Platform requires integration to their backup platform. Which two configurations are supported? (Choose two.)

- A. direct tape connectivity
- B. serverless backup
- C. NDMP v4 backup over the LAN
- D. block level backup direct to tape

Correct Answer: AC

QUESTION 2

Your customer is using iSCSI LUNs on a Hitachi NAS Platform. Which three Hitachi NAS file system management functions will the customer be able to use? (Choose three.)

- A. snapshots
- B. SnapMirror
- C. NVRAM logging
- D. iLUN expansion
- E. Quotas

Correct Answer: ACE

QUESTION 3

A customer is considering deploying a Hitachi NAS Platform in their environment. They require a single mount point to allow for ease of administration and data organization. Which licensed Hitachi NAS Platform software feature would help this customer?

- A. storage pools
- B. snapshots
- C. File System Rollback (FSR)
- D. Cluster Namespace (CNS)

Correct Answer: D

QUESTION 4



You are planning a data migration from a distributed Windows file server environment to a Hitachi NAS platform. You have discovered that some of the applications use hard-coded IP addresses. You have also identified that login scripts are used to map network drives for the end users. Which two methods can you use to minimize impact during the migration? (Choose two.)

- A. Modify the login scripts to point to the new location regardless of host name or IP address.
- B. Use CNAME records to preserve the IP addresses for hard-coded applications.
- C. Use the same IP addresses on the EVSs as the original server for applications.
- D. Use CNS to present a unified namespace and transparently migrate the applications.

Correct Answer: AC

QUESTION 5

A customer is asking for a detailed description of clustering technology on the Hitachi NAS Platform cluster with multiple GbE ports in the aggregates. Which two statements describe the automatic failover behavior? (Choose two.)

- A. Only the EVS affected by a problem will failover to another node.
- B. All EVS will failover when a GbE port in an aggregation fails.
- C. An EVS will failover when all GbE ports in an aggregation used by an EVS fail.
- D. An EVS will not failover when all GbE ports used by an EVS fail.

Correct Answer: AC

[Latest HH0-450 Dumps](#)

[HH0-450 VCE Dumps](#)

[HH0-450 Study Guide](#)