



# HP2-T23<sup>Q&As</sup>

Supporting Industry Standard Server Solutions

**Pass HP HP2-T23 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hp2-t23.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Which tools should you use to identify correctable memory errors on a ProLiant Gen8 server that has an operating system without HP management agents installed? (Select two)

- A. iLO
- B. System Management Home page
- C. Active Health System
- D. ACU
- E. ROM

Correct Answer: AC

---

### QUESTION 2

What are features of the HP ProLiant MicroServer? (Select two.)

- A. Sound level of at least 85 DBa
- B. SATA 3.5 inch LFF drives
- C. SAS 2.5 inch SC hot-plug drives
- D. AMD processor
- E. Intel processor
- F. Fibre Channel drives

Correct Answer: BD

---

### QUESTION 3

What do you need to manage and control an InfiniBand fabric?

- A. A subnet manager
- B. Amezzanine connector
- C. System Management Homepage
- D. Version Control Agent

Correct Answer: A

---



#### QUESTION 4

Which statements are correct about HP Systems Insight Manager (HP SIM) 7.0 Agentless Management? (Select two.)

- A. HP SIM communicates with the CPU and collects essential data for the operating system.
- B. Agentless Management is provided by the CPU.
- C. HP SIM communicates with the iLO Management Engine to collect hardware data.
- D. The Agentless Management Service runs on the host to provide software information directly to the iLO Management Engine.

Correct Answer: CD

---

#### QUESTION 5

What should an administrator do to prevent discharge of static electricity when replacing components in a ProLiant server? (Select two.)

- A. Place the server blade on a flat, level surface.
- B. Wear a plastic grounding strap to remove the ESD-sensitive component from the static safe container
- C. Place the ESD-sensitive component on a grounded surface.
- D. Wear a cloth grounding strap to replace the defective component.
- E. Avoid hand contact with the ESD-sensitive component by transporting in a static-safe container.

Correct Answer: BE

[HP2-T23 PDF Dumps](#)

[HP2-T23 VCE Dumps](#)

[HP2-T23 Practice Test](#)