



JN0-102^{Q&As}

Juniper Networks Certified Internet Associate, Junos(JNCIA-Junos)

Pass Juniper JN0-102 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-102.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the default route preference value for EIGRP?

- A. 20
- B. 100
- C. 170
- D. 200

Correct Answer: C

QUESTION 2

-- Exhibit -user@router> show route inet.0: 9 destinations, 9 routes (9 active, 0 holddown, 0 hidden)

```
+ = Active Route, - = Last Active, * = Both 10.10.10.91/32 *[Direct/0] 00:09:40 >via lo0.0 10.10.10.92/32 *[OSPF/10]
00:01:50, metric 1 >to 172.16.1.2 via ge-0/0/2.0 100.100.1.0/24 *[Static/5] 00:01:50 Reject 172.16.1.0/24 *[Direct/0]
00:06:09 >via ge-0/0/2.0 172.16.1.1/32 *[Local/0] 00:06:09 Local via ge-0/0/2.0 192.168.0.0/16 *[Aggregate/130]
00:00:06
```

```
Reject 192.168.0.0/17 *[Aggregate/130] 00:00:06 >to 172.16.1.2 via ge-0/0/2.0 192.168.50.0/24 *[Static/5] 00:00:06 >to
172.16.1.2 via ge-0/0/2.0 192.168.51.0/24 *[Static/5] 00:00:06 >to 172.16.1.2 via ge-0/0/2.0 user@router> show
configuration policy-options policy-statement demo { term 1 { from { route-filter 192.168.0.0/16 longer accept;
}
}
```

```
then reject; } } user@router> show configuration protocols ospf export demo; area 0.0.0.0 { interface ge-0/0/2.0; } --
Exhibit -Given the configuration and routing table shown in the exhibit, which routes will be advertised to OSPF
```

neighbors because of the demo policy?

- A. 192.168.0.0/16 only
- B. 192.168.0.0/17 only
- C. 192.168.50.0/24 and 192.168.51.0/24
- D. 192.168.0.0/17, 192.168.50.0/24, and 192.168.51.0/24

Correct Answer: D

QUESTION 3

Which statement is true about logical units?

- A. Logical units are similar to VLANs used by other vendors.
- B. A logical unit is required for transit interfaces.



- C. Frame Relay encapsulation supports one logical unit.
- D. Link speed and duplex are configured in the logical unit properties.

Correct Answer: B

QUESTION 4

Which CLI command is used to display output one page at a time?

- A. user@router> show interfaces | no-more
- B. user@router> show interfaces | trim
- C. user@router> show interfaces
- D. user@router> show interfaces | display

Correct Answer: C

QUESTION 5

Which two statements are true regarding an Ethernet collision domain? (Choose two.)

- A. If a switch is used, the collision domain is limited to each device and the switch.
- B. If a hub is used, the collision domain is limited to each device and the hub.
- C. If a hub is used, the collision domain includes all devices connected to the hub.
- D. If a switch is used, the collision domain includes all devices connected to the switch.

Correct Answer: AC

[JN0-102 VCE Dumps](#)

[JN0-102 Practice Test](#)

[JN0-102 Study Guide](#)