



JN0-343^{Q&As}

Juniper Networks Certified Internet Specialist (JNCIS-ENT)

Pass Juniper JN0-343 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-343.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When is MAC limiting performed on a frame from an unknown source MAC address?

- A. when the ingress PFE sends header information to RE
- B. when the ingress PFE performs a MAC address lookup
- C. when the PFE adds the MAC address to the bridge table
- D. when the RE adds the MAC address to the bridge table

Correct Answer: A

QUESTION 2

Which three statements are true regarding BGP peers? (Choose three.)

- A. BGP peers can reside in the same AS or different ASs.
- B. BGP peers on the same router must all use the same peer AS number.
- C. External BGP peers have a default TTL value of 1.
- D. External BGP peers will always accept the AS path, origin, and next-hop attributes from their neighbors.
- E. Internal BGP routers will propagate IBGP learned routes to other IBGP peers by default.

Correct Answer: ACD

QUESTION 3

What is the minimum configuration necessary to create two VLANs and two operational RVIs?



```
Ⓐ set interfaces ge-0/0/0.0 family ethernet-switching vlan members Vlan10
set interfaces ge-0/0/1.0 family ethernet-switching vlan members Vlan11
set vlans Vlan10 vlan-id 10
set vlans Vlan10 l3-interface vlan.10
set vlans Vlan11 vlan-id 11
set vlans Vlan11 l3-interface vlan.11

Ⓑ set interfaces ge-0/0/0.0 family ethernet-switching vlan members Vlan10
set interfaces ge-0/0/1.0 family ethernet-switching vlan members Vlan11
set interfaces vlan unit 10 family inet address 10.0.10.1/24
set interfaces vlan unit 11 family inet address 10.0.11.1/24
set vlans Vlan10 vlan-id 10
set vlans Vlan10 l3-interface vlan.10
set vlans Vlan11 vlan-id 11
set vlans Vlan11 l3-interface vlan.11

Ⓒ set interfaces vlan unit 10 family inet address 10.0.10.1/24
set interfaces vlan unit 11 family inet address 10.0.11.1/24
set vlans Vlan10 vlan-id 10
set vlans Vlan10 l3-interface vlan.10
set vlans Vlan11 vlan-id 11
set vlans Vlan11 l3-interface vlan.11

Ⓓ set interfaces ge-0/0/0.0 family ethernet-switching vlan members Vlan10
set interfaces ge-0/0/1.0 family ethernet-switching vlan members Vlan11
set interfaces vlan unit 10 family inet address 10.0.10.1/24
set interfaces vlan unit 11 family inet address 10.0.11.1/24
set vlans Vlan10 vlan-id 10
set vlans Vlan11 vlan-id 11
```

A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: B

QUESTION 4

Which instance type is used when configuring filter-based forwarding?

A. vrf

B. forwarding

C. virtual-router

D. fbf

Correct Answer: B



QUESTION 5

Which command verifies that graceful Routing Engine switchover (GRES) is operational?

- A. show system switchover on the master RE
- B. show system switchover on the backup RE
- C. show task replication on the master RE
- D. show task replication on the backup RE

Correct Answer: B

[Latest JN0-343 Dumps](#)

[JN0-343 Study Guide](#)

[JN0-343 Exam Questions](#)