



JN0-532^{Q&As}

FWV, Specialist (JNCIS -FWV)

Pass Juniper JN0-532 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/JN0-532.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which command is used to verify that IGMP is running correctly?

- A. get route igmp
- B. get igmp query
- C. set igmp query interface e0/1
- D. exec igmp interface e0/1 query

Correct Answer: D

QUESTION 2

Which three elements are required to configure route redistribution on a ScreenOS device? (Choose three.)

- A. a filter map
- B. a route map
- C. an export rule
- D. an access list
- E. a redistribution list

Correct Answer: BCD

QUESTION 3

What must be configured differently for a route-based VPN and a policy-based VPN?

- A. proxy-id
- B. proposals
- C. remote gateway type
- D. binding the tunnel interface

Correct Answer: D

QUESTION 4

You have configured NSRP Active/Passive using the default vsd-group. You are using BGP to learn routes from adjacent network devices. You want each firewall to establish a BGP peer to different upstream routers. You also want the backup device to learn dynamic routes.



Which configuration would ensure you can establish a BGP peer to two different routers?

- A. Configure two BGP peers on the same VSI interface, but use a different virtual router on each device.
- B. Use the `unset vr nsrp-config-sync` command and configure BGP peers on the VSI interface.
- C. Use the `unset nsrp vsd-group id 0` and `set nsrp vsd-group id 1` commands for VSI interfaces, then configure BGP peers on the local interfaces, then `unset vr untrust-vr nsrp-config-sync`.
- D. Use the `unset nsrp vsd-group id 0` and `set nsrp vsd-group id 1` commands for the VSI interfaces, then configure BGP peers on the local interfaces, then `unset vr nsrp-config- sync`.

Correct Answer: D

QUESTION 5

What should you configure to ensure an HA cable failure does not result in both devices attempting to become master?

- A. failover count
- B. secondary path
- C. monitor threshold
- D. heartbeat threshold

Correct Answer: B

[JN0-532 PDF Dumps](#)

[JN0-532 VCE Dumps](#)

[JN0-532 Exam Questions](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.passapply.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket:



 <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.
All trademarks are the property of their respective owners.
Copyright © passapply, All Rights Reserved.