



JN0-533^{Q&As}

FWV, Specialist (JNCIS-FWV)

Pass Juniper JN0-533 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-533.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Referring to the exhibit, which three statements are true? (Choose three.)

NS5200(M)-> get nsrp nsrp version: 2.0 cluster info: cluster iD. 1, name. 5200 local unit iD. 8000208 active units discovered. index: 0, unit iD. 8014208, ctrl maC. 0010db000085, data maC. 0010db000086 index: 1, unit iD. 8337344, ctrl maC. 0010db0000c5, data maC. 0010db0000c6 total number of units: 2 VSD group info: init hold time. 5 heartbeat lost threshold. 3 heartbeat interval: 200(ms) master always exist: enabled group priority preempt holddown ineligible master PB other members 0 50 yes 45 no myself 8330044 total number of vsd groups: 1 Total iteration=,time=878546093,max=4900,min=170,average=18 RTO mirror info: run time object sync. enabled ping session sync. enabled coldstart sync done nsrp data packet forwarding is enabled nsrp link info: control channel: ha1 (ifnum: 5) maC. 0010db000085 state. up data channel: ha2 (ifnum: 6) maC. 0010db000086 state. up ha secondary path link not available NSRP encryption: disabled NSRP authentication: disabled device based nsrp monitoring threshold. 255, weighted sum: 0, not failed device based nsrp monitor interface. ethernet2/1(weight 255, UP) ethernet2/3(weight 255, UP) ethernet2/4(weight 255, UP) ethernet2/5(weight 255, UP) ethernet2/2 (weight 255, UP) device based nsrp monitor zone. device based nsrp track ip: (weight: 255, disabled) number of gratuitous arps: 4 (default) config sync. enabled track ip: disabled

- A. This cluster is configured as an active/active cluster.
- B. RTO sync is enabled.
- C. No secondary path is configured.
- D. master-always-exists is enabled.
- E. Only one interface is used for both the control and data links.

Correct Answer: BCD

QUESTION 2

Which action does a ScreenOS device perform first when processing a packet?

- A. It checks for an existing session.
- B. It checks for attacks in the payload.
- C. It performs a route lookup.
- D. It performs a policy lookup.

Correct Answer: A

QUESTION 3

What is the default timeout for a fully established TCP session?

- A. 10 minutes
- B. 30 seconds



- C. 30 minutes
- D. 300 seconds

Correct Answer: C

QUESTION 4

Which two statements are true about redundant interfaces on a ScreenOS device? (Choose two.)

- A. With two interfaces in a redundant interface, only one link is primary at any given time.
- B. On high-end models with multi-ASIC cards, redundant Ethernet ports must be in the same ASIC group.
- C. With two interfaces in a redundant interface, both links pass traffic at the same time.
- D. On high-end models with multi-ASIC cards, redundant Ethernet ports can be used on different ASIC groups.

Correct Answer: AB

QUESTION 5

You are creating a DIP pool of 30 addresses. You would like to see how addresses are being allocated to different traffic streams. Which command will you use to view this information?

- A. snoop
- B. get dip all
- C. get session
- D. get address xlate

Correct Answer: C

[JN0-533 PDF Dumps](#)

[JN0-533 VCE Dumps](#)

[JN0-533 Study Guide](#)