



# PW0-105<sup>Q&As</sup>

Certified Wireless Network Administrator (CWNA)

## Pass EC-COUNCIL PW0-105 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/pw0-105.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EC-COUNCIL Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

As XYZ Company's wireless specialist, you have been asked to troubleshoot some unexpected frame patterns in a wireless protocol capture. Your peers explain that the network's beacon frames are inconsistent. That is, the BSSID is the same for all beacons, but the source address varies between three different addresses.

What network configuration would cause this beacon frame behavior?

- A. A single AP supports multiple BSSs with different SSIDs
- B. A virtual cell single channel network has been implemented
- C. The beacons are from an IBSS instead of a BSS
- D. Three APs still share the same default configuration.

Correct Answer: C

---

### QUESTION 2

What statements describe industry practices for communication protocols between WLAN controllers and controller-based APs? (Choose two)

- A. All vendors use the same protocol so that APs will interoperate with WLAN controllers from other vendors.
- B. Some vendors use proprietary protocols, and some vendors use protocols based on public standards like RFCs.
- C. For most vendors, the controller-based APs maintain data and control tunnels with at least two controllers for immediate failover and redundancy.
- D. All vendors support at least one L2 or L3 broadcast protocol for controller discovery by controller-based APs.
- E. All vendors recommend using L2 (instead of L3) controller discovery and tunneling protocols in large enterprises.

Correct Answer: BD

---

### QUESTION 3

Which data rate is supported by 802.11g radios that is not supported by 802.11a radios?

- A. 9 Mbps
- B. 11 Mbps
- C. 12 Mbps
- D. 54 Mbps
- E. 65 Mbps
- F. 130 Mbps



Correct Answer: B

---

#### QUESTION 4

What WLAN system feature is required to produce a scenario with the following configuration on a single access point?  
(Choose 2)

1.

SSID = Guest / BSSID = AA:AA:AA:AA:AA:AA /

VLAN = 22 / Subnet = 192.168.22.0 / RF Channel = 6

2.

SSID = Corporate / BSSID = BB:BB:BB:BB:BB:BB /

VLAN = 33 / Subnet = 192.168.33.0 / RF Channel = 6 / User Type A

3.

SSID = Corporate / BSSID = BB:BB:BB:BB:BB:BB /

VLAN = 44 / Subnet = 192.168.44.0 / RF Channel = 6 / User Type B

- A. Multiple WLAN Profiles
- B. Call Admission Control
- C. Virtual Cell with SCA
- D. Access Categories
- E. User-based authentication
- F. Dual-radio AP hardware
- G. Integrated DHCP server

Correct Answer: AE

---

#### QUESTION 5

What component of the 802.11 standard allows stations to reserve access to the RF medium for a specified period of time?

- A. Long slot times
- B. DTIM Interval
- C. Listen Interval
- D. Probe Request frames



E. RTS or CTS frames

Correct Answer: E

[Latest PW0-105 Dumps](#)

[PW0-105 Practice Test](#)

[PW0-105 Exam Questions](#)