



C2150-609^{Q&As}

IBM Security Access Manager V9.0 Deployment

Pass IBM C2150-609 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/c2150-609.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

The customer currently maintains all its users in Active Directory. As part of its new IBM Security Access Manager (ISAM) V9.0 deployment, the customer understands it will have to implement the ISAM "Global Sign-on (GSO)" to archive SSO with certain backend applications which do their own authentication and cannot be modified.

Which federated repositories configuration will address the customer requirements?

- A. Use an external ISDS LDAP as the ISAM primary LDAP, federate with the AD and import all AD users into the ISAM TDS.
- B. Configure the AD as the ISAM Primary LDAP, which will create the necessary secauthority= default suffix. Import all users into the ISAM AD.
- C. Use the ISAM embedded LDAP as the Primary LDAP, federate with the AD and configure "basic user", and specify "basic-user-principal-attribute= samAccountName"
- D. Use an external ISDS LDAP as the Primary LDAP, federate with the AD, configure "basic user", specify "basic-user-principal-attribute= samAccountName" and "basic-user-suffix= secauthority=default".

Correct Answer: C

QUESTION 2

The web security department of an organization has found that their site is vulnerable to Denial of Service, Brute Force, Buffer Overflow and decided to use the Web Application Firewall (WAF) feature available in IBM Security Access Manager V9.0.

Even after enabling WAF, the site is still vulnerable to the above attacks. The deployment professional is pretty sure that the signature for these attacks have been released and has decided to check for X-Force updates.

How should the deployment professional check and update this?

- A. Using CLI, firmware -> ips_updt_install
- B. Using CLI, updates -> xforce_updt_install
- C. Using LMI, Manage System Settings -> Updates and Licensing -> Available Updates
- D. Using LMI, Manage System Settings -> Updates and Licensing -> Intrusion Prevention updates

Correct Answer: C

QUESTION 3

The request in a customer environment is IDP Initiated unsolicited SSO. The initial URL is:

<https://POCIDP/FIM/sps/saml2idp/saml20/loginitial?>

RequestBinding =HTTPPostandPartnerId= <https://POCSP/isam/sps/abc/saml20andNameIdFormat =Email>



The POCIDP is Point of Contact for Identity Provider and POCSP is Point of Contact for Service Provider.

The customer wants to configure TargetURL within the Service Provider Federation configuration in IBM Security Access Manager V9.0.

What will satisfy this requirement?

- A. poc.signin.responseTargetURL
- B. Target_URL in the mapping rule
- C. Federation Runtime property TargetURL
- D. itfim_override_targeturl_attr in the mapping rule

Correct Answer: D

QUESTION 4

To configure IBM Security Access Manager V9.0 for Windows desktop single sign-on using Kerberos authentication, the Reverse Proxy's identity in the Active Directory Kerberos Domain must be associated with a Service Principal name (SPN).

Given the following information:

AD Kerberos Realm Name: company.com ISAM Reverse Proxy DNS Domain: ws1.company.com

What is the correct SPN?

- A. HTTP/ws1.company.com
- B. HTTP/ws1.company.com@COMPANY.COM
- C. HTTP/ws1.company.com@ws1.company.com
- D. HTTP/ws1.company.com@WS1.COMPANY.COM

Correct Answer: B

QUESTION 5

An IBM Security Access Manager (ISAM) V9.0 deployment professional has downloaded a snapshot from an ISAM virtual appliance configured with reverse proxy. This snapshot is being applied to another virtual appliance.

Which condition must be met before applying a snapshot from one virtual appliance to another?

- A. Both appliances must be in the same time zone
- B. Both appliances must be at the same firmware level
- C. Both appliances must have same application database setting



D. Both appliances must have the same activation keys applied.

Correct Answer: B

[Latest C2150-609 Dumps](#)

[C2150-609 PDF Dumps](#)

[C2150-609 Practice Test](#)