



C9530-410^{Q&As}

IBM MQ V8.0 System Administration

Pass IBM C9530-410 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/c9530-410.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A system administrator needs to collect monitoring data on an AIX system for performance analysis purposes. The system administrator needs to find out how many messages are put on and retrieved from a queue, and the total number of bytes that the queue processes during a configured interval. How can the system administrator enable the collection of the required data and set the interval to 15 minutes?

- A. Set the ACCTMQION and the STATINT900 for the queue manager.
- B. Set the queue MONQON a ribute and set the interval in the queue a ribute AMONQINTI5.
- C. Set the STATMQION on the queue manager and the queue, and set the interval in the queue manager a ribute STATINTI5.
- D. Set the queue manager and the queue STATQON a ributes, and the interval in the queue manager a ribute STATINT900.

Correct Answer: A

QUESTION 2

A system administrator was asked by an application team to find out when their queue manager running on IBM i System was started.

Which Command Language CL command should the system administrator run?

- A. DSPMQM
- B. DSPMQMQ
- C. DSPMQMSTS
- D. DSPMQMCSVR

Correct Answer: C

QUESTION 3

An application using the WebSphere MQ classes for JMS encountered an error. A First Failure Support Technology FFST file has been created named JMS0001.FDC. Which default directory should the system administrator review?

- A. /var/mqm/errors
- B. /var/mqm/errors/FFDC
- C. /var/mqm/qmgrs/QMGRNAME/errors/FFDC
- D. current application working directory/FFDC



Correct Answer: B

QUESTION 4

There is a requirement to create a development queue manager on AIX with authorization checks disabled.

How can a system administrator do this?

- A. Set environment variable MQSNOAUT=yes before creating the queue manager.
- B. Set SecurityPolicy=none on Service stanza in qm.ini file then start the queue manager.
- C. Start the queue manager with the MQSNOAUT environment variable set to "YES".
- D. Create the queue manager and then run the setmqaut command with the -remove all attribute.

Correct Answer: A

QUESTION 5

QUEUE1 has messages from an uncommitted unit of work. Which command can the system administrator use to find the name of the application connected to QUEUE1?

- A. DISPLAY QUEUE QUEUE1 ALL
- B. DISPLAY THREAD * TYPE INDOUBT
- C. DISPLAY QSTATUS QUEUE1 TYPE QUEUE ALL
- D. DISPLAY QSTATUS QUEUE1 TYPE HANDLE ALL

Correct Answer: D

[C9530-410 PDF Dumps](#)

[C9530-410 Exam Questions](#)

[C9530-410 Braindumps](#)