CAU301^{Q&As}

CyberArk Sentry

Pass CyberArk CAU301 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/cau301.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CyberArk Official Exam Center

🔧 **Instant Download** After Purchase

🔧 **100% Money Back** Guarantee

🔧 **365 Days** Free Update

🔧 **800,000+** Satisfied Customers

QUESTION 1

In a SIEM integration it is possible to use the fully-qualified domain name (FQDN) when specifying the SIEM server address(es)

A. TRUE

B. FALSE

Correct Answer: A

QUESTION 2

A vault admin received an email notification that a password verification process has failed Which service sent the message?

A. The PrivateArk Server Service on the Vault.

B. The CyberArk Password Manager service on the Components Server.

C. The CyberArk Event Notification Engine Service on the Vault

D. The CyberArk Privileged Session Manager service on the Vault.

Correct Answer: C

QUESTION 3

When a DR vault server becomes an active vault, it will automatically fail back to the original state once the primary vault comes back online.

A. True, this is the default behavior

B. False, this is not possible

C. True, if the \\'AllowFailback\\' setting is set to yes in the PADR.ini file.

D. True if the \\'AllowFailback\\' setting is set to yes in the dbparm mi file

Correct Answer: A

QUESTION 4

Which of the following are secure options for storing the contents of the Operator CD, while still allowing the contents to be accessible upon a planned Vault restart? Choose all that apply

A. Store the CD in a physical safe and mount the CD every time vault maintenance is performed.

B. Copy the contents of the CD to the System Safe on the vault

C. Copy the contents of the CD to a folder on the vault server and secure it with NTFS permissions.

D. Store the server key in a Hardware Security Module.

E. Store the server key in the Provider cache

Correct Answer: E

QUESTION 5

If a transparent user matches two different directory mappings, how does the system determine which user template to use?

A. The system will use the template for the mapping listed first.

B. The system will use the template for the mapping listed last.

C. The system will grant all of the vault authorizations from the two templates.

D. The system will grant only the vault authorizations that are listed in both templates

Correct Answer: C