



CWDP-303^{Q&As}

Certified Wireless Design Professional

Pass CWNP CWDP-303 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/cwdp-303.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

You are validating association capabilities from clients to an 802.1X/EAP secure SSID. The RADIUS server's IP address is 10.100.50.25 and the default RADIUS authentication port is used. When testing them, none of the clients are able to associate to the SSID. Troubleshooting the WLAN infrastructure, you found out that the server is up and the RADIUS service is up as well, but the authenticator is not able to communicate properly with the server. What's your next troubleshooting step?

- A. Verify that the shared secret between the authenticator and the RADIUS server is correct
- B. Reboot the clients
- C. Reboot the server
- D. Restart the RADIUS service

Correct Answer: A

QUESTION 2

What are the deliverables to your customer after successfully implementing a WLAN infrastructure?

- A. Digital or physical assets, guides, floorplans and configuration documents
- B. Project Charter
- C. Facility blueprints
- D. Nothing is required. The implemented WLAN was deliverable

Correct Answer: A

QUESTION 3

Your customer is using PSK as their only authentication. They have an industry requirement to move to a stronger solution. Your recommendation is to move to a certificate-based type of authentication where both the client and server require certificates. Which EAP type would be the best fit?

- A. EAP-FAST
- B. EAP-TTLS
- C. EAP-TLS
- D. PEAP

Correct Answer: C

Reference: <https://www.intel.com/content/www/us/en/support/articles/000006999/network-and-io/wirelessnetworking.html>

**QUESTION 4**

A business traveler from North America is in Europe. The hotel only provides coverage in 2.4 GHz. The traveler connects to the hotel's SSID and notices an AP in the hotel room. However, the laptop reports a very low RSSI when connected. The traveler does not have the same problem when connecting in the lobby. What would be the most likely cause of the low RSSI in the hotel room?

- A. The AP in the room is using ZigBee instead of Wi-Fi.
- B. The AP in the room is transmitting on channel 13 and the traveler associated to a non-channel 13 AP located elsewhere.
- C. The switchport that the AP is connected to is only capable of transmitting at 10 Mbps.
- D. The AP in the room is using Bluetooth instead of Wi-Fi.

Correct Answer: C

QUESTION 5

After designing a WLAN infrastructure using predictive design software. What's the best way to validate the predictive design in the physical space before deployment, if time and budget allow for it?

- A. Deploy all of the APs as they're shown in the predictive design and perform an active site survey.
- B. Deploy all of the APs as they're shown in the predictive design and perform a passive site survey.
- C. Use a client device positioned where the APs will be installed and measure the signal from the client device.
- D. Perform an AP-on-a-Stick survey using AP locations based upon the predictive design to confirm each AP's placement.

Correct Answer: D

Reference: <https://vectorusa.com/steps-to-designing-and-deploying-wireless-lan/>

[CWDP-303 VCE Dumps](#)

[CWDP-303 Study Guide](#)

[CWDP-303 Exam Questions](#)