



DES-1121^{Q&As}

Specialist - Implementation Engineer PowerMax and VMAX Family
Solutions Version 1.0

Pass EMC DES-1121 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/des-1121.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A systems administrator is performing a configuration change on a PowerMax array. Where does the configuration manager perform the change?

- A. Host which performs the change
- B. MMCS
- C. Disk drives
- D. SYMAPI

Correct Answer: B

QUESTION 2

What is a minimum requirement for Dell EMC VSI 8.0 on a VMAX All Flash array?

- A. Unisphere 8.x
- B. Unisphere 9.x
- C. 5977 1125.1125
- D. 5977.1131.1131

Correct Answer: C

QUESTION 3

You have just presented storage to an ESXi server and want to rescan the storage adapter to ensure the server can see the new volume Based on recommended best practices, what is the preferred method to perform this task?

- A. Use the vSphere VSI plugin to rescan the entire cluster
- B. Run the command from a non-cluster host using the ESX CLI
- C. Use the vSphere Client to perform the rescan of the host
- D. Run the command from the ESXi server with the ESX CLI enabled

Correct Answer: A

QUESTION 4

Which service has to be manually started first when Unisphere services are down?

- A. SMASDB



B. SYMEVENT

C. SMAS

D. SMI-S

Correct Answer: C

<https://www.dell.com/support/kbdoc/en-ca/000167303/powermax-vmax-all-flash-and-unisphere-for-powermax-smas-service-does-not-start-for-new-installation-of-unisphere-for-powermax-on-rhel-platform>

QUESTION 5

From an application perspective what should be done prior to performing an SRDF Fallback operation?

A. Continue accessing the R2 devices Start accessing the R1 devices before running the command

B. Stop accessing the R2 devices Run the command and then start accessing the R1 devices

C. Stop accessing the R2 devices Start accessing the R1 devices before running the command

D. Continue accessing the R2 devices Run the command and then start accessing the R1 devices

Correct Answer: B

[DES-1121 Practice Test](#)

[DES-1121 Exam Questions](#)

[DES-1121 Braindumps](#)