



DES-1241^{Q&As}

Specialist - Platform Engineer, PowerStore

Pass Dell DES-1241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/des-1241.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Dell Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which Dell EMC PowerStore model reserves the last two slots of the base enclosure for NVMe NVRAM?

- A. 3000
- B. 5000
- C. 7000
- D. 9000

Correct Answer: A

Reference: <https://www.dell.com/en-us/collaterals/unauth/white-papers/products/storage/h18241-dell-emc-powerstore-best-practices-guide.pdf> (9)

QUESTION 2

During Dell EMC PowerStore startup, both appliance nodes have rebooted in service mode. What must be done first to avoid management software conflicts?

- A. Reboot node B
- B. Clear the boot mode
- C. Disable node B boot mode
- D. Return node A to normal mode

Correct Answer: D

Reference: <https://www.dell.com/support/manuals/pk/en/pkbsd1/powerstore-1000/pwrstr-isg/power-control-procedure-considerations?guid=guid-4352c94e-0ae7-4a2e-8593-9ae135bb9e34andlang=en-us>

QUESTION 3

What is an alternative way to collect logs instead of using the Dell EMC PowerStore manager GUI?

- A. Data Collect using Service Container
- B. USB stick inserted into the system
- C. Data Collect using vCenter
- D. Discovery Utility

Correct Answer: A

Data Collection, Data Collects (DCs), or Service Data.



Reference: <https://www.dell.com/support/kbdoc/en-pk/000133407/powerstore-how-to-generate-and-collect-various-logs-from-powerstore>

QUESTION 4

A Storage Administrator needs to address specific fixes within their Dell EMC PowerStore system. Which NDU software upgrade option is used for this situation?

- A. Hotfixes
- B. vCenter
- C. Drive firmware
- D. Software releases

Correct Answer: B

A PowerStore software upgrade fails if the PowerStore X model cluster cannot communicate with the vCenter Server during the upgrade. Reference: https://downloads.dell.com/manuals/common/pwrstr-2-0-1-rn_en-us.pdf

QUESTION 5

How is a service laptop IP configured to connect to the Service LAN port of a Dell EMC PowerStore node?

- A. Static IP: 128.221.1.249 and netmask: 255.255.255.0
- B. Obtain IP address from DHCP on PowerStore
- C. Static IP: 169.254.1.249 and netmask: 255.0.0.0
- D. Leave IP address and netmask unconfigured

Correct Answer: A

The service laptop being used to connect to the Service LAN Ports should be configured with:

1.

IP: 128.221.1.249

2.

Mask: 255.255.255.0 Reference: <https://www.dell.com/support/kbdoc/en-pk/000130356/powerstore-ssh-and-powerstore-manager-access-using-the-service-lan-ports>