



DES-1721^{Q&As}

Specialist - Implementation Engineer-SC Series Exam

Pass EMC DES-1721 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/des-1721.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Why should Legacy Port Mode be selected rather than Virtual Port Mode on an SC Series storage array?

- A. Virtual Port Mode requires NPIV support
- B. Legacy Port Mode is easier to set up and more reliable
- C. Virtual Port Mode is difficult to set up
- D. Virtual Port Mode does not support ALUA

Correct Answer: C

QUESTION 2

When connecting directly to an SC7020 storage array using Dell Storage Manager Client, which host/IP address is entered into the login screen?

- A. Data Collector IP address of the Storage Center
- B. Management IP address of the Storage Center
- C. Bottom Storage Controller Management IP address
- D. Top Storage Controller Management IP address

Correct Answer: A

Reference: <https://www.dell.com/storagehelp/dellstorageclient/2016R2/en-us/GUID-931D776E-64AC-4826-A20C-8988C94F2A9C.html>

QUESTION 3

DRAG DROP

You have just deployed an SC Series array in Virtual Port Mode. What is the correct sequence of steps to perform an array port failover test?

Select and Place:



Confirm I/O is being received on the selected volume in the DSM GUI	STEP 1
Physically disconnect the port that matches the identified controller port	STEP 2
Send I/O from the host to an existing single path volume on the array	STEP 3
Confirm I/O is still being received on the selected volume in the DSM GUI	STEP 4
Confirm the WWN for the controller port intended to failover in the DSM GUI	STEP 5

Correct Answer:

	Confirm I/O is being received on the selected volume in the DSM GUI
	Physically disconnect the port that matches the identified controller port
	Send I/O from the host to an existing single path volume on the array
	Confirm the WWN for the controller port intended to failover in the DSM GUI
	Confirm I/O is still being received on the selected volume in the DSM GUI

QUESTION 4

What is the maximum memory supported on a single SC9000 controller?

- A. 64 GB
- B. 96 GB
- C. 128 GB
- D. 256 GB

Correct Answer: D



Reference: <https://www.dell.com/en-us/work/shop/povw/storage-sc9000>

QUESTION 5

Which SC Series array feature allows all front-end ports to act as active data paths?

- A. Dual Fabric
- B. ALUA
- C. Virtual Port Mode
- D. Legacy Port Mode

Correct Answer: C

Reference: <https://www.dell.com/storagehelp/dellstorageclient/2016R3/en-us/GUID-2D6A2482-F78D-4598-ADA3-D9E49ED3ED7F.html>

[Latest DES-1721 Dumps](#)

[DES-1721 Exam Questions](#)

[DES-1721 Braindumps](#)