DES-6321 Q&As

Specialist - Implementation Engineer - VxRail Appliance Exam

Pass EMC DES-6321 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/des-6321.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC Official Exam Center

Instant Download After Purchase
100% Money Back Guarantee
365 Days Free Update
800,000+ Satisfied Customers

QUESTION 1

When using VxRail Manager, what is the source of information that can help validate good VxRail system post-deployment status?

A. Last Heartbeat, Last Configuration Sent, Network Environment Settings, Cluster Monitor

B. System Diagnostic, Events, Health Logical View, Health Physical View, Log Bundle

C. MARVIN-Virtual-SAN-Cluster > Manage > Health and Performance

D. MARVIN-Virtual-SAN-Cluster > Monitor > Virtual SAN > Health

Correct Answer: C

QUESTION 2

You are validating that a network environment is ready for a 4 node VxRail Model V570F deployment. What types of DNS records must be created for VxRail components before implementation can begin?

A. Forward (A) records only

B. Forward (A) records and Reverse (PTR) records

C. Forward (A) and MX records

D. NS records and Reverse (PTR) records

Correct Answer: B

Reference: https://www.dellemc.com/en-us/collaterals/unauth/technical-guides-support-information/products/converged-infrastructure/h15300-vxrail-network-guide.pdf (30)

QUESTION 3

A VxRail Cluster setup with P570F nodes is used for product evaluation purposes at customer sites. Before moving the Cluster to another customer site, it needs to be reset.

Where is the image located to complete this task?

A. SATADOM

B. IDSDM

C. BOSS

D. MB Server

Correct Answer: B

QUESTION 4

A workstation is being configured on the management VLAN (10.150.140.0/24) to connect to VxRail Manager for first time deployment.

Configuring which IP addresses on the workstation will result in a successful deployment without having to change them during initialization?

A. 192.168.1.199 and 10.150.140.100

B. 192.168.1.250 and 10.150.140.255

C. 192.168.10.199 and 10.150.140.255

D. 192.168.10.250 and 10.150.140.250

Correct Answer: A

QUESTION 5

You are attempting to reset a single G Series node running 4.0.x code to the factory default. You discover that the configbundle.tgz file is corrupt.

What is the recommended method to recover the node?

A. Rapid Appliance Self Recovery

B. Node Replacement

C. Mobile Build Server

D. Reset Script

Correct Answer: C

Latest DES-6321 Dumps DES-6321 VCE Dumps DES-6321 Practice Test