DNDNS-200^{Q&As}

DNDNS-200^{Q&As}

Dell Networking Professional Exam

Pass Dell DNDNS-200 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/dndns-200.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Dell Official Exam Center

QUESTION 1

A networking engineer needs to configure several VLANs for S-Series switches for both Untagged and Tagged traffic.

Which three of the following apply? (Choose three.)

A. A Tagged interface can only be a member of a single Tagged VLAN.

B. A Tagged interface can be a member of multiple VLANs.

C. Hybrid ports can be assigned to both an Untagged VLAN and Tagged VLAN.

D. When a Tagged interface is removed from a VLAN, it will always be placed in the default VLAN as a Tagged interface.

E. Hybrid ports can be assigned to multiple VLANs but not the default VLAN.

F. When a Tagged interface is removed from a VLAN, it will remain Tagged only if it is Tagged in another VLAN.

Correct Answer: BCF

QUESTION 2

When facing the front of a C-Series switch, in which direction does air flow?

A. from the right side to left side

B. from the front side to back side

C. from the back side to front side

D. from the left side to right side

Correct Answer: A

QUESTION 3

Refer to the output.

```
router bgp 200
neighbor internal peer-group
neighbor internal remote-as 200
neighbor internal update-source loopback 0
neighbor internal route-map set-med out
neighbor internal filter-list 1 out
neighbor internal filter-list 2 in
neighbor 172.68.232.54 peer-group internal
neighbor 172.68.232.55 peer-group internal
neighbor 172.68.232.56 peer-group internal
neighbor 172.68.232.57 filter-list 3 in
```

According to the partial configuration, which two things have occurred? (Choose two.)

A. All the configured neighbors are in autonomous system 200.

B. Three AS-path filters are applied to each BGP neighbor.

C. The peer group shortens the IBGP configuration.

D. Only the outgoing filters are applied to BGP updates.

E. The peer group shortens the EBGP configuration.

Correct Answer: AC

QUESTION 4

Which three components can be used to deploy 10GbE N-Series switches in a user-port stack configuration? (Choose three.)

A. SAS Cables

B. Standard Ethernet Cables

C. Dedicated stacking modules

D. TwinAx Cables

E. Optical Transceivers

Correct Answer: ADE

QUESTION 5

On an S-Series switch, what two events occur when a static null route has been configured in the system to drop a packet? (Choose two.)

A. Null route is installed in the PBR table to drop the packet

B. Null route is saved into the running configuration.

C. Null route is installed in the ACL table with deny statement.

D. Null route is installed in the IP forwarding table.

Correct Answer: BD

DNDNS-200 PDF Dumps   DNDNS-200 VCE Dumps   DNDNS-200 Practice Test