



E22-285^{Q&As}

VxRail Appliance 4.x Deployment and Implementation Exam

Pass EMC E22-285 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/e22-285.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

When adding a VxRail node the validation fails. What could be the cause of this problem?

- A. IPv6 multicasting is not enabled
- B. Only one network interface online
- C. Time on the node was not set correctly
- D. DNS record was not created

Correct Answer: B

QUESTION 2

When using the RASR method to reset a VxRail node, which boot device is selected?

- A. RASRUSB
- B. SATADOM
- C. IDRAC SD CARD
- D. IDSMD

Correct Answer: D

QUESTION 3

The Market Place on a VxRail Manager is empty on a newly deployed system. Testing shows that the Internet is reachable through proxy in the management network. Which action should be taken to correct this situation?

- A. VxRail Manager has no proxy support.
- B. Upgrade to latest version and add proxy configuration manually.
- C. Manually add the proxy information in the VxRail Manager configuration
- D. Reset the appliance and redeploy with proxy information filled in the deployment process.

Correct Answer: B

QUESTION 4

A planned VxRail deployment will use an External vCenter Server and syslog server. Which ping connectivity tests should succeed and which should fail before the deployment?

- A. Succeed: ESXi hosts and syslog Fail: VxRail Manager and vCenter



B. Succeed: VxRail Manager and ESXi hostsFail: vCenter and syslog server

C. Succeed: vCenter and syslog serverFail: VxRail Manager and ESXi hosts

D. Succeed: VxRail Manager and syslogFail: vCenter and ESXi hosts

Correct Answer: A

QUESTION 5

During a node add procedure the new node cannot be discovered. A ping to the IPv6 address is responding.

What could be the cause of this issue?

A. Only one network interface is up on the new node

B. vSAN VLAN is not configured correctly

C. Management VLAN ID is not set on the vmk0 interface

D. Loudmouth process is not running

Correct Answer: A

[Latest E22-285 Dumps](#)

[E22-285 VCE Dumps](#)

[E22-285 Braindumps](#)