



E22-285^{Q&As}

VxRail Appliance 4.x Deployment and Implementation Exam

Pass EMC E22-285 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/e22-285.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by EMC
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

During the deployment of VxRail, you import a JSON file and attempt a validation. An error indicates that node 1 cannot access the other nodes. When you look at the Nexus switchport configuration, you see the following on all VxRail ports: interface TenGigabitEthernet 1/x switchport switchport trunk switchport trunk allow vlan all What is a possible reason for this situation?

- A. "switchport trunk native vlan x" is not configured
- B. "switchport access vlan x" is not configured
- C. "switchport trunk vlan x" is not configured
- D. "switchport vlan x" is not configured

Correct Answer: B

QUESTION 2

When adding an S Series node to a Gen 2 VxRail 240F cluster the build fails. What could be a possible cause of this situation?

- A. IP Pool has no more free addresses
- B. Hybrid and Flash nodes cannot be mixed in the same cluster
- C. Quanta and Dell hardware cannot be mixed in the same cluster
- D. Loudmouth process needs to be restarted

Correct Answer: B

QUESTION 3

What is the Dell EMC product that is purpose-built for departmental and edge applications, as well as small enterprise and mid-market data centers?

- A. Vscale Architecture
- B. VxRail
- C. VxRack
- D. Vblock/VxBlock

Correct Answer: B

QUESTION 4



A 4 node VxRail solution will be deployed. Based on the exhibit, what will be the host name assigned to the last node in the cluster?

ESXi hostname prefix	host	MyVxRail
Seperator	None or -	-
Iterator	Num 0X (for 01,02,03,04...) or Num X (for 1,2,3,4...) or Alpha (for a,b,c,d...)	Alpha
Domain	localdomain.local	mycompany.com

- A. MyVxRaild.mycompany.com
- B. MyVxRail-4.mycompany.com
- C. MyVxRail-d.mycompany.com
- D. MyVxRail04.mycompany.com

Correct Answer: C

QUESTION 5

A company has indicated that they do not want to change the native VLAN for their entire switch. Based on best practice, how should the Top of Rack (ToR) switch be configured?

- A. Set the native VLAN on the switch ISL ports
- B. The native VLAN for the switch must be set
- C. Set the native VLAN only at the VxRail trunk ports
- D. Do not configure ToR switch native VLAN and instead tag the VLAN on VxRail

Correct Answer: A

[Latest E22-285 Dumps](#)

[E22-285 Study Guide](#)

[E22-285 Exam Questions](#)