



EX294^{Q&As}

Red Hat Certified Engineer (RHCE) exam for Red Hat Enterprise Linux
8 Exam

Pass RedHat EX294 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/ex294.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by RedHat
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

SIMULATION

You are working as an Administrator. There is a common data shared (/data) from 192.168.0.254 to all users in your local LAN. When user's system start, shared data should automatically mount on /common directory.

A.

Correct Answer: Please see explanation

QUESTION 2

Install and configure ansible

User bob has been created on your control node. Give him the appropriate permissions on the control node. Install the necessary packages to run ansible on the control node.

Create a configuration file /home/bob/ansible/ansible.cfg to meet the following requirements:

The roles path should include /home/bob/ansible/roles, as well as any other path that may be required for the course of the sample exam.

The inventory file path is /home/bob/ansible/inventory.

Ansible should be able to manage 10 hosts at a single time.

Ansible should connect to all managed nodes using the bob user.

Create an inventory file for the following five nodes:

node1.example.com

node2.example.com

node3.example.com

node4.example.com

node5.example.com

Configure these nodes to be in an inventory file where node1 is a member of group dev, node2 is a member of group test, node3 is a member of group proxy, node4 and node 5 are members of group prod. Also, prod is a member of group

webservers.

A. Answer: See the for complete Solution below.

Correct Answer: A

```
In/home/sandy/ansible/ansible.cfg [defaults] inventory=/home/sandy/ansible/inventory
roles_path=/home/sandy/ansible/roles remote_user= sandy host_key_checking=false [privilegeescalation] become=true
```



become_user=root become_method=sudo become_ask_pass=false

In /home/sandy/ansible/inventory [dev] node 1 .example.com [test] node2.example.com [proxy] node3 .example.com [prod] node4.example.com node5 .example.com [webservers:children] prod

QUESTION 3

```
# getenforce 1
# vim /etc/sysconfig/selinux
    SELINUX=enforcing
```

SIMULATION

Please open the ip_forward and take effect permanently.

A.

Correct Answer: Please see explanation

QUESTION 4

```
# yum install -y postfix
# service postfix restart
# chkconfig postfix on
# vim /etc/postfix/main.cf
    inet_interfaces = all
    mydestination = example.com, domain30.example.com, localhost
    mynetworks = 172.16.30.0/24, 127.0.0.1/8
# services postfix restart
```

Test:

```
# netstat -tulnp |grep 25
# hostname
# echo hello |mail -s "test"root@example.com
# cat /var/spool/mai/harry
```

Connect to the email server and send email to admin, and it can be received by harry.

A. Answer: See the for complete Solution below.

Correct Answer: A



```
# vim /etc/aliases
admin: harry
# newaliases
```

QUESTION 5

Please open the ip_forward and take effect permanently.

A. Answer: See the for complete Solution below.

Correct Answer: A

```
# vim /etc/sysctl.conf
net.ipv4.ip_forward = 1
# sysctl -w (takes effect immediately)
```

If no "sysctl.conf" option, use these commands:

```
# sysctl -a |grep net.ipv4
# sysctl -P net.ipv4.ip_forward = 1
# sysctl -w
```

[Latest EX294 Dumps](#)

[EX294 Practice Test](#)

[EX294 Braindumps](#)