



F50-531^{Q&As}

BIG-IP v10.x LTM Essentials V10.x

Pass F5 F50-531 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/f50-531.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by F5 Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

What is the purpose of floating self-IP addresses?

- A. to define an address that grants administrative access to either system at any time
- B. to define an address that allows either system to initiate communication at any time
- C. to define an address that allows network devices to route traffic via a single IP address
- D. to define an address that gives network devices greater flexibility in choosing a path to forward traffic

Correct Answer: C

QUESTION 2

Assume a virtual server has a ServerSSL profile. What SSL certificates are required on the pool members?

- A. No SSL certificates are required on the pool members.
- B. The pool members' SSL certificates must only exist.
- C. The pool members' SSL certificates must be issued from a certificate authority.
- D. The pool members' SSL certificates must be created within the company hosting the BIG-IPs.

Correct Answer: B

QUESTION 3

As a part of the Setup Utility, the administrator sets the host name for the BIG-IP. What would be the result if the two systems in a redundant pair were set to the same host name?

- A. Host names do not matter in redundant pair communication.
- B. In a redundant pair, the two systems will always have the same host name. The parameter is synchronized between the systems.
- C. The first time the systems are synchronized the receiving system will be assigned the same self-IP addresses as the source system.
- D. When the administrator attempts to access the configuration utility using the host name, they will always connect to the active system.

Correct Answer: C

QUESTION 4

Which IP address will the client address be changed to when SNAT automap is specified within a Virtual Server



configuration?

- A. The floating self IP address on the VLAN where the packet leaves the system.
- B. The floating self IP address on the VLAN where the packet arrives on the system.
- C. It will alternate between the floating and non-floating self IP address on the VLAN where the packet leaves the system so that port exhaustion is avoided.
- D. It will alternate between the floating and non-floating self IP address on the VLAN where the packet arrives on the system so that port exhaustion is avoided.

Correct Answer: A

QUESTION 5

What is the purpose of MAC masquerading?

- A. to prevent ARP cache errors
- B. to minimize ARP entries on routers
- C. to minimize connection loss due to ARP cache refresh delays
- D. to allow both BIG-IP devices to simultaneously use the same MAC address

Correct Answer: C

[Latest F50-531 Dumps](#)

[F50-531 VCE Dumps](#)

[F50-531 Braindumps](#)