

# H12-221<sup>Q&As</sup>

HCIP-Routing & Switching-IERS V2.5

# Pass Huawei H12-221 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.passapply.com/h12-221.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



# https://www.passapply.com/h12-221.html

2024 Latest passapply H12-221 PDF and VCE dumps Download

#### **QUESTION 1**

The process of determining the shortest path can	be divided into two	phases: determine	transit node first,	and then
determine the stub network.				

A. TRUE

B. FALSE

Correct Answer: B

#### **QUESTION 2**

Route filtering can filter not only routing information but also link-state information.

A. TRUE

B. FALSE

Correct Answer: B

### **QUESTION 3**

What is the default LOCAL\_PREF and PREFERRED-VALUE assigned to routes in a VRP system?

A. 0,32768

B. 100,0

C. 255,100

D. 32768,0

Correct Answer: B

## **QUESTION 4**

What command must be configured to establish a BGP connection between indirectly connected EBGP peers?

A. peer connect-interface

B. peer valid-ttl-hops

C. peer ignore

D. peerebgp-max-hop

Correct Answer: D

## https://www.passapply.com/h12-221.html 2024 Latest passapply H12-221 PDF and VCE dumps Download

#### **QUESTION 5**

Which of the following statements regarding NSSA commands is false?

- A. The default-route-advertise command is used to generate a type-7 default route.
- B. The no-import-route parameter prevents the import of AS external routes in the form of Type-7 LSAs into an NSSA.
- C. The no-summary parameter prevents the advertisement of Type-3 and Type-4 LSAs in an area.
- D. The set-n-bit parameter indicates that an N-bit will be set in a DD packet.

Correct Answer: A

H12-221 Practice Test

H12-221 Study Guide

H12-221 Braindumps