



# H12-222<sup>Q&As</sup>

HCIP-Routing & Switching-IENP V2.5

## Pass Huawei H12-222 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/h12-222.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





### QUESTION 1

When BFD detection intervals at both ends are 30ms and 40ms. Which of the following statement is true?

- A. A BFD session can be set up. After the negotiation, the detection interval of 40ms is used.
- B. A BFD session can be set up. After the negotiation, the detection interval of 30ms is used.
- C. A BFD session can be set up, and packets are sent at respective intervals at both ends.
- D. A BFD session cannot be established.

Correct Answer: A

---

### QUESTION 2

MPLS is a label forwarding technology, Which of the following MPLS statements is false?

- A. MPLS uses the connection-oriented control plane and connectionless data plane.
- B. The control plane transmits route information and distributes labels. The data plane transmits packets along the created label switched path (LSP).
- C. Switches in an MPLS domain only need to forward packets based on the label added before the IP header.
- D. Compared with traditional IP forwarding, MPLS label forwarding greatly improves the data forwarding efficiency.

Correct Answer: A

---

### QUESTION 3

MPLS uses LDP to provide different label distribution modes. Which of the following statements regarding LDP label distribution control modes are false? (Multiple Choice)

- A. LDP label distribution can be controlled in ordered mode.
- B. In ordered mode, when an LSR is the origin of a route, it can send label mapping messages to the upstream router initiatively and does not need to wait for label mapping messages from the next hop LSR.
- C. LDP label distribution cannot be controlled in independent mode.
- D. In independent mode, an LSR cannot send label mapping messages to the upstream router before it receives label mapping messages from the next hop LSR.

Correct Answer: CD

---

### QUESTION 4

What is the BFD version number supported by VRP?



- A. Version 1
- B. Version 2
- C. Version 3
- D. Version 4

Correct Answer: A

---

#### QUESTION 5

Which of the following statements regarding MAC address spoofing attacks is false?

- A. Attackers initiate MAC address spoofing attacks using the MAC address learning mechanism.
- B. Attackers send data frames with forged MAC address to the switch to initiate MAC address spoofing attacks.
- C. When MAC address spoofing attacks occur, the switch may learn incorrect mapping between MAC addresses and IP addresses.
- D. When MAC address spoofing attacks occur, the switch may send packets to the attacker.

Correct Answer: C

[H12-222 PDF Dumps](#)

[H12-222 VCE Dumps](#)

[H12-222 Exam Questions](#)