H12-711 Q&As

HCIA-Security V4.0

Pass Huawei H12-711 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/h12-711.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei Official Exam Center

- **Instant Download** After Purchase
- **100% Money Back** Guarantee
- **365 Days** Free Update
- **800,000+** Satisfied Customers

QUESTION 1

In order to ensure the normal remote L2TP dial-up users to access the corporate network,the user is required to assign an IP address within the enterprise network services and resources to be accessed not on the same network segment (without considering the ARP Proxy technology).

A. True

B. False

Correct Answer: A

QUESTION 2

Network Address Port Translation (NAPT) and Network Address Translation (NAT)whatis the difference? (Choose two)

A. After NAPT conversion for users outside the network,all packets from the same IP address or IP address of a few

B. NAT only supports application layer protocol address translation

C. NAPT only supports network layer protocol address translation

D. NAT support network layer protocol address translation

Correct Answer: AD

QUESTION 3

SVN3000 product extensions supported by the network access methods,including what?(Choose three)

A. Full- channel mode (Full Tunnel)

B. Separation channel mode (Split Tunnel)

C. Routing (route Tunnel)

D. Manually (Manual Tunnel)

Correct Answer: ABD

QUESTION 4

What are Web proxy implementations?(Choose two)

A. Web-link

B. Web rewritten

C. Web Forwarding

D. Web pass-through

Correct Answer: AB

QUESTION 5

As illustrated connection : PC1 ----- SW1 ---------- SW2 ----- PC2; SW1 two ports defined for VLAN1 access type port,SW2 two ports defined as VLAN 2 access port type,(PC1 and PC2 in the same subnet) then the following description is correct?

A. Because all access port,in fact, do not pass VLAN tag information, so you can access PC1 PC2.

B. Because VLAN SW2 SW1 and the ends are different, so youcannotcommunicate between two PC.

C. If two switches are connected to the port is set to trunk ports, two PC can communicate.

D. Because PVID default port on the switch is VLAN 1, so the PC can be both visits.

Correct Answer: A

Latest H12-711 Dumps H12-711 PDF Dumps H12-711 Practice Test