



H12-811^{Q&As}

HCIA-Datacom V1.0

Pass Huawei H12-811 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/h12-811.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Network switch A and router A are connected by two links. The two links are aggregated in manual load sharing mode. The aggregated port number is 1, and the aggregated link needs to carry VLAN TAG100 when forwarding data. The switch When A uses a trunk link, which of the following configurations need to be used by switch A? ()

- A. 4
- B. 5
- C. 3

Correct Answer: B

QUESTION 2

The administrator plans to implement route backup by configuring static floating routes. The correct way to achieve this is ()

- A. The administrator needs to configure different metric values for the main static route and the standby static route
- B. The administrator needs to configure different TAGs for the main static route and the standby static route
- C. The administrator only needs to configure two static routes
- D. The administrator needs to configure different protocol priority values for the main static route and the standby static route

Correct Answer: D

QUESTION 3

The Layer 2 Ethernet switch generates entries in the MAC address table according to the () of the Ethernet frame received by the port. ()

- A. Source MAC. Address
- B. Destination MAC. Address
- C. Destination IP address

Correct Answer: B

QUESTION 4



Which of the following commands can be used to query the configuration information of the device's OSPF protocol?
()*

- A. dis ip routing-table
- B. Enter the command "display t in the OsPF protocol view. his\ ,.: ,.:

Correct Answer: AB

QUESTION 5

In the OSPF protocol, the correct one in the following description of DR is (). ()*

- A. Establish an adjacency relationship between DR and BDR
- B. If the priority values of the two routers are equal, the router with the larger Router ID is selected as the DR
- C. By default, all routers in this broadcast network will participate in the DR election
- D. If the priority values of the two routers are different, the router with the smaller priority value is selected as the DR

Correct Answer: ABC

[H12-811 PDF Dumps](#)

[H12-811 Practice Test](#)

[H12-811 Exam Questions](#)