



H12-811^{Q&As}

HCIA-Datacom V1.0

Pass Huawei H12-811 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/h12-811.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which of the following parameters need to be considered when electing a root port in STP? (*)

- A. Port priority
- B. Port slot number, such as G0/0/1
- C. Duplex mode of the port
- D. The cost of the port reaching the root switch
- E. MAC address of E port

Correct Answer: ABD

QUESTION 2

The network structure and OSPF partition are shown in the figure. In the figure, except for RTA., the routers RTB, RT and RT are ABR routers. ()

(RTA) ip route-static 10.1.1.0 24 12.1.1.1 permanent

(RTA) ip route-static 10.2.2.0 24 13.1.1.1.

- A. True
- B. False

Correct Answer: B

QUESTION 3

The MAC address table of existing switches is shown in the figure. Which of the following statements are correct? ()
(Single-choice question) Huawei display mac address MAC address table of slot 0: MAC Address VLAN/PEVLAN CEVLAN Port Type LSP/LSR-ID VSI/SI MAC-Tunnel 5489 9811 0b49 1 Eth0/0/3 static 0/ Total matching items on slot 0 displayed =1

MAC address table of slot 0: MAC Address VLAN/ PEVLAN CEVLAN Port Type LSP/LSR-ID VSI/SI MAC-Tunnel 5489-989d-1d30 1 Eth0/0/1 dynamic 0/5489-9885-18a8 1 Eth0/0/2 dynamic 0/Total matching items on slot 0 displayed 2

- A. The MAC address 5489-9811-0b49 is manually configured by the administrator
- B. After the switch restarts, all MAC addresses need to be relearned
- C. The MAC address 5489-989d-1d30 is manually configured by the administrator
- D. The MAC address 5489-9885-18a8 is manually configured by the administrator



Correct Answer: A

QUESTION 4

A company applies for a IP address segment, which needs to be evenly distributed to 8 subsidiaries. The largest subsidiary has 14 computers. Different subsidiaries must be in different network segments, so the subnet mask should be set. for()

A. 255.255.255.240

B. 255.255.255.0

C. 255.255.255.128

Correct Answer: B

QUESTION 5

What kind of network equipment can host A and host B use to achieve communication?

A. router

B. Hub

C. HUB

D. Layer 2 switch

Correct Answer: A

[Latest H12-811 Dumps](#)

[H12-811 Practice Test](#)

[H12-811 Study Guide](#)