



# H12-831<sup>Q&As</sup>

HCIP-Datacom-Advanced Routing & Switching Technology V1.0

## Pass Huawei H12-831 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/h12-831.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

You have set IS-IS IPv6 enable under the interface, what is the meaning of this command?

- A. Activate on the interfaceIPv6 IS-ISprocess1
- B. Activate on the interfaceIPv6 IS-ISprocess3
- C. activate on the interfaceIPv6 IS-ISprocess10
- D. activate on the interfaceIPv6 IS-ISprocess2

Correct Answer: A

---

#### QUESTION 2

What is the value of the linkage between OSPF and BFD?

- A. OSPFohelloThe sending interval is in seconds, more thanBFDInduction link status is fast
- B. BFDThe message sending interval can reach the millisecond level, which is less thanOSPFInduction link status is slow
- C. Detected at the millisecond levelBFD. associationOSPFstate, fulfilledOSPFThe purpose of quickly sensing the status of the tank
- D. BFDAny change in state will not affectOSPFneighbor state

Correct Answer: C

---

#### QUESTION 3

Which of the following actions may affect the normal operation of the customer's network?

- A. Device naming
- B. software upgrade
- C. Hardware expansion
- D. Routing Protocol Configuration Changes

Correct Answer: BCD

---

#### QUESTION 4

Does the role of Link-LSA in OSPFv3 not include?

- A. To the other road on the link Tiandikou noon-



- B. Advertise this router's interface to other routers on the linkID
- C. Advertise the link-local address of this interface to other routers on the link
- D. Advertise to other routers on the link the originatingNetwork-LSAOptions set in

Correct Answer: A

---

#### QUESTION 5

In BGPIMPLS IP VPN, if the OSPF protocol is used between PEs and CEs to exchange routing information, the domain identifier (Domain ID) is used to distinguish whether the incoming routes in the VPI instance come from the same OSPF domain.

- A. True
- B. False

Correct Answer: A

[H12-831 PDF Dumps](#)

[H12-831 VCE Dumps](#)

[H12-831 Study Guide](#)