



# H12-891<sup>Q&As</sup>

HCIE-Datacom V1.0

## Pass Huawei H12-891 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/h12-891.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





#### QUESTION 1

In addition to stateless address autoconfiguration, IPV6 devices can also obtain addresses, gateways, DNS, and other information through DHCPv6

- A. True
- B. False

Correct Answer: B

---

#### QUESTION 2

IPSGs can statically configure binding tables or form binding tables by using them with DHCP-Snooping

- A. True
- B. False

Correct Answer: A

---

#### QUESTION 3

In an MPLS IBGP VPN environment, if tags are distributed only through BGP, LDP, the MPLS tags for a message can be up to two layers of tags.

- A. True
- B. False

Correct Answer: A

---

#### QUESTION 4

There is an existing router running OSPF connected to Zone 0 and Zone 1 You configured Zone 1 as a stub zone, what classes does LSA that only operates inside Zone 1 include?

- A. 7 ? LSA
- B. 1 ? LSA ? 2 ? LSA
- C. 1 LSA,2 LSA 5 LSA
- D. 3 ? LSA ? 4 ? LSA
- E. 1 LSA,2 LSA 3 LSA

Correct Answer: E

---



### QUESTION 5

Regarding the MPLS basic forwarding process, the following description is incorrect? Radio

- A. By default, the PHP-enabled Erass node assigns a label value of 3 to the inverted second-hop node.
- B. When an IP message enters the MPLS domain, the MPLS boundary device inserts a new label between the layer 2 header and the IP header.
- C. When the P message enters the MPLS domain, check whether the Tunel ID value corresponding to the destination IP address is Ox0O If the Tunel IID value is Ox0 Then enter the MPLS forwarding process.
- D. The transport node device replaces the existing top-of-stack label (outermost label) with the label assigned by the next hop device.

Correct Answer: C

[Latest H12-891 Dumps](#)

[H12-891 PDF Dumps](#)

[H12-891 Braindumps](#)