H13-511_V4.0 Q&As

HCIA Cloud Computing V4.0

Pass Huawei H13-511_V4.0 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/h13-511_v4-0.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Huawei
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

In FusionCompute, the administrator binds the two network adapters of the CNA host in the active / standby mode. After binding, the transmission rate is equal to the sum of the transmission rates of the two network ports.

A. TRUE

B. FALSE

Correct Answer: B

QUESTION 2

In a NAS environment, multiple hosts writing to a file at the same time will cause data consistency issues.

A. True

B. False

Correct Answer: A

QUESTION 3

In Huawei FusionCompute, the following incorrect description of the security group rule is.

A. When a virtual machine has multiple network cards, you can configure a security group for each network card.

B. A virtual machine can communicate with the outside world only after a security group is created and rules are added.

C. All virtual machine NICs in the same security group will use the security group rules for access control

D. The essence of a security group is a collection of rules

Correct Answer: B

QUESTION 4

In Huawei FusionCompute, the following incorrect description of port groups and security groups is

A. A virtual machine NIC is connected to a virtual port in the port group, and a virtual machine NIC is associated with a security groupA

B. B-port group is a collection of one or more virtual ports on a DVS, while a security group is a collection of one or more rules

C. A DVS can have multiple port groups and a VM can be protected by multiple security groups

D. Security groups are based on port groups to protect virtual machines /// virtual network cards

Correct Answer: D

QUESTION 5

The configuration of a Huawei switch port is as follows: Interface GigabitEhernet 0/0/1 Port link-type access Port default vlan 16 According to the above configuration, the following statement is correct

A. This port will add a VLAN 16 tag to the data frames that pass by

B. This port allows only data with vlan 16 tags to pass through.

C. The port will strip the VLAN 16 label of the passing data frame and forward it.

D. The port will not do any operations on the data frames passing by.

Correct Answer: C

H13-511_V4.0 Practice Test   H13-511_V4.0 Study Guide   H13-511_V4.0 Exam
Questions