



HCE-3210^{Q&As}

Hitachi Vantara Certified Specialist - NAS Solutions Architect

Pass Hitachi HCE-3210 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hce-3210.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You are designing a solution to replace a customer's existing NetApp FAS3140. The customer uses Snapshot and SnapMirror to provide local snapshots and DR protection. They perform a daily snapshot which is retained for 30 days and they execute SnapMirror on a 15 minute interval. In the event of a failover to the DR site, all the locally executed snapshots are available for use on the DR system. How should you configure snapshot rules with replication to provide equivalent capabilities?

- A. on the source system that is by the object replication policy
- B. on the source and target systems using two different object replication policies, one of which both snapshot rules
- C. on the target system only by the object replication policy
- D. on the source and target systems using a single object replication policy

Correct Answer: B

QUESTION 2

You have prepared a solution upgrade proposal for an existing Hitachi NAS Platform customer who is planning to purchase additional nodes. While presenting to your customer, they ask about mixing models within a cluster.

Which statement is correct?

- A. A cluster must be made of the same models.
- B. A cluster can be made of different models.
- C. Mixing 3000 models within a cluster is supported.
- D. All models can be clustered with each other.

Correct Answer: A

QUESTION 3

You are designing Hitachi NAS File Clone solution for a customer with an existing Hitachi NAS platform. Which two are required? (Choose two.)

- A. NAS firmware version 8.x or later
- B. iSCSI volumes



- C. WFS-2 file system
- D. Hitachi NAS G2 hardware

Correct Answer: AC

QUESTION 4

A customer plans to consolidate several multimedia servers that support jumbo frames into a Hitachi NAS Platform 4000 cluster.

What must be done before increasing the MTU size in the HNAS 4000 system?

- A. Increase the MTU size in the Ethernet switch.
- B. Disable VLAN tagging.
- C. Disable Link Aggregation Control Protocol (LACP).
- D. Verify that all components in the path support jumbo frames.

Correct Answer: D

QUESTION 5

A customer with a Hitachi NAS Platform 3200 (source) would like to relocate all the data to a new Hitachi NAS Platform 4000 (destination) using Incremental File Replication with Transfer Primary Access (TPA). Which two are required before the data migration can take place? (Choose two.)

- A. The source and destination firmware levels of the HNAS systems must be compatible for replication.
- B. The external SMU must manage the source and destination nodes.
- C. The source and destination nodes must be connected to different storage systems.
- D. The clients of the source and destination nodes must have write access to the snapshots before and after the replication.

Correct Answer: AB
