



HCE-3700^{Q&As}

Hitachi Vantara Certified Expert - Performance architect

Pass Hitachi HCE-3700 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hce-3700.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A user with a diskless VSP G800 uses ShadowImage from the G800 with a virtualized VSP G200 system. Application performance suffers during the frequent ShadowImage resynchronization operations.

What should be done to reduce the impact of the ShadowImage throughput in this scenario?

- A. Configure both sets of disks into an HDT pool and let the HDT scheme manage the different workloads.
- B. Define the ShadowImage target volumes to use dedicated external FC paths using dedicated RAID groups.
- C. Set Copy to 15.
- D. Increase the VSP G800 cache size to improve the application cache hit rates.

Correct Answer: A

QUESTION 2

You are planning for a performance upgrade for a transaction application.

Which three metrics are necessary to determine the required back-end storage configuration in this scenario? (Choose three.)

- A. cache read hit ratio
- B. read/write ratio
- C. transfer rates
- D. queue depth
- E. IOPS

Correct Answer: ABE

QUESTION 3

Which three key metrics are required for sizing applications? (Choose three.)

- A. cache read hit ratios
- B. IOPS
- C. I/O read/write ratios
- D. number of BED pairs
- E. port speed

Correct Answer: ABC



QUESTION 4

How does the HDLM Extended Round Robin algorithm impact sequential I/O?

- A. It continues to use the same path for a user-specified count of sequential I/O requests.
- B. It remembers a user-determined number of addresses to better implement sequence detection for the storage.
- C. It buffers and reorders I/O requests to improve sequence detection by the storage.
- D. It makes a path decision for every I/O request.

Correct Answer: A

References: <https://dokumen.tips/documents/dynamic-link-manager-hitachi-vantara-support-file-systems-for-hdlmwhen-volume.html>

QUESTION 5

A customer with a VSP G1000 is using HDT with SAS 15K drives and external storage. The customer wants the daytime response-sensitive workload to benefit from tiering. They also want to minimize the impact of relocations on the daytime operation itself.

In this scenario, which action will satisfy the requirements?

- A. Enable monitoring only during the daytime hours (9:00 AM to 5:00 PM) and only enable relocation at other times.
- B. Disable monitoring during daytime hours (9:00 AM to 5:00 PM)
- C. Enable active flash so that all relocations can be completed in short bursts.
- D. Use continuous mode with a 30-minute cycle time and define relocation during daytime hours (9:00 AM to 5:00 PM) with a low relocation speed.

Correct Answer: A

[Latest HCE-3700 Dumps](#)

[HCE-3700 PDF Dumps](#)

[HCE-3700 Study Guide](#)