



HCE-3700^{Q&As}

Hitachi Vantara Certified Expert - Performance architect

Pass Hitachi HCE-3700 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hce-3700.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer has an HDP pool with four array groups and 600 GB SAS drives operating at 85% utilization. Four array groups of the same configuration were added to the pool.

In this scenario, which metric should be reviewed to validate optimal pool performance?

- A. pool total IOPS
- B. pool I/O profile
- C. pool array group utilization
- D. pool read/write ratio

Correct Answer: C

QUESTION 2

Your customer has a VSP G1000 with an HDT pool with two tiers (SAS 15K and SAS 10K). The response times have increased over time to an unacceptable level. They want to add a flash tier and they ask you if this solution will be appropriate.

Which tool should you use to satisfy the requirement?

- A. Hitachi Server Priority Manager
- B. Hitachi Tiered Storage Manager
- C. Hitachi Universal Volume Manager
- D. Tier Properties Performance Graph

Correct Answer: D

QUESTION 3

A customer using a small block interactive workload on a VSP G200 complains about poor application performance. They use an FC SAN which consists of 8 Gbps and 16 Gbps FC switches.

What are two causes of the performance issue? (Choose two.)

- A. Front-end ports of the VSP G200 are connected to the 8 Gbps FC switch.
- B. The front-end FC ports are used by another bandwidth-intensive application.
- C. The host HBA has an insufficient queue depth setting.
- D. The multi-pathing software uses round robin balancing algorithm.

Correct Answer: BC



QUESTION 4

You are planning for a performance upgrade for a transaction application.

Which three metrics are necessary to determine the required back-end storage configuration in this scenario? (Choose three.)

- A. cache read hit ratio
- B. read/write ratio
- C. transfer rates
- D. queue depth
- E. IOPS

Correct Answer: ABE

QUESTION 5

A customer complains about high response times. This occurs frequently with bursts of write I/O at 6,000 IOPS for 10 second periods during each minute. The write response is 60 ms during these 10 second periods. The average IOPS rate reported by Hitachi Tuning Manager over 1 minute is 600.

In this scenario, what is the average response time over 1 minute?

- A. 10 ms
- B. 30 ms
- C. 60 ms
- D. 90 ms

Correct Answer: A

[HCE-3700 PDF Dumps](#)

[HCE-3700 Practice Test](#)

[HCE-3700 Exam Questions](#)