



HP0-Y52^{Q&As}

Applying HP FlexNetwork Fundamentals

Pass HP HP0-Y52 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hp0-y52.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Refer to the exhibit.

```
Provision-1(config)# show spanning-tree 1,19,21 instance ist
<-output omitted->
```

Port	Type	Cost	Priority	Role	State	Designated Bridge
1	100/1000T	20000	128	Designated	Forwarding	d4c9ef-851680
19	100/1000T	20000	128	Root	Forwarding	d07e28-cec94f
21	100/1000T	20000	128	Alternate	Blocking	d07e28-ced31e

This switch currently assigns all VLANs to Multiple Spanning Tree Protocol (MSTP) instance 0 or the Internal Spanning Tree (IST). Which statement correctly describes interface 21?

- A. The interface is down at Layer 2; it is not available for sending or receiving any traffic.
- B. The interface is an edge port but has received Bridge Protocol Data Units (BPDUs), so it is disabled.
- C. The interface does not forward or accept data traffic, but it is ready to start forwarding if interface 19 fails.
- D. The interface does not support spanning tree; it is possible that it will introduce a loop in the network.

Correct Answer: C

QUESTION 2

A customer is implementing an access layer solution with four HP Comware switches in an Intelligent Resilient Framework (IRF) virtual device or domain. The customer expects to add two additional switches of the same model and would like to add them to the existing IRF virtual device. What must the customer verify?

- A. that the IRF virtual device has spanning tree enabled on it
- B. that the new switches are both assigned the same member ID as the master of the existing IRF virtual device
- C. that the IRF virtual device is using a daisy chain topology to provide better resilience
- D. that the switch model supports at least six switches in an IRF virtual device

Correct Answer: A

QUESTION 3

In the HP Software-defined Networking (SDN) architecture, what connects the Application layer to the physical device or Infrastructure layer?

- A. HP Network Automation
- B. HP SDN Controller



C. HP IMC Virtual Network Manager (VNM)

D. HP IMC SDN Manager

Correct Answer: B

QUESTION 4

A network administrator deletes old files in the flash file system of an HP Comware switch. The administrator then notices that the amount of free space available has not changed. Which command must the administrator execute to free up the space from deleted files?

A. reset recycle-bin

B. recycle-bin cleanup

C. cleanup recycle-bin

D. recycle-bin empty

Correct Answer: A

QUESTION 5

A network administrator plans to execute show commands as well as make configuration changes. Which HP ProVision privilege role must be assigned to an account for the administrator to do this?

A. Operator

B. Administrator

C. Superuser

D. Manager

Correct Answer: D

[Latest HP0-Y52 Dumps](#)

[HP0-Y52 PDF Dumps](#)

[HP0-Y52 Braindumps](#)