



Implementing HP MSM Wireless Networks

Pass HP HP2-Z32 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/hp2-z32.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

😳 365 Days Free Update

800,000+ Satisfied Customers





QUESTION 1

What is the primary difference between AES-CCMP and TKIP?

- A. With AES-CCMP, each station generates its PMK as part of the 802.1X authentication process.
- B. With TKIP, the station uses the same key to secure data and the MIC.
- C. AES-CCMP uses a 254-bit key stream, while TKIP uses a 128-bit key stream.
- D. AES-CCMP uses a stronger encryption algorithm than that provided by TKIP.

Correct Answer: D

QUESTION 2

A company has an environment with multiple HP MSM Controllers that do not form a team. The company wants to control which controllers manage which APs. What is one feature that network administrators can implement for this purpose?

- A. provisioning of the APs\\' 802.1X supplicant settings
- B. AP authentication
- C. MAC address filters
- D. controller interface discovery settings

Correct Answer: B

QUESTION 3

A company has an MSM720 Controller and wants to implement a team solution. What is the guideline for implementing teaming with MSM720 Controllers?

- A. The team can include a maximum of five members, which must have a Premium license.
- B. The team can include a maximum of five members, which must have a Mobility license.
- C. The team can include a maximum of two members, which must both have a Premium Mobility license.
- D. The team can include a maximum of three members, which must have a Teaming license.

Correct Answer: C

QUESTION 4


A company requires a wireless Access Point (AP) that supports Multiple-in, Multiple-Out (MIMO) and three spatial streams. Which HP MSM AP provides these capabilities?



A. MSM310 B. MSM317 C. MSM430 D. MSM460 Correct Answer: D

QUESTION 5

Refer to the exhibit.



The exhibit shows a VSC setting that is disabled. A network administrator is creating an access- controlled VSC for guest access. Which use case does disabling this setting impact?

- A. The company has central RADIUS servers and web servers, which it wants to use to authenticate guests.
- B. The controller is part of a teaming solution.
- C. Guests need to log into the controller\\'s local pages to receive access to any resources.
- D. Guests need to receive access to resources on their local subnet before authenticating.

Correct Answer: D

HP2-Z32 Practice Test

HP2-Z32 Study Guide

HP2-Z32 Braindumps