



HP2-Z34^{Q&As}

Building HP FlexFabric Data Centers

Pass HP HP2-Z34 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hp2-z34.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

What is the purpose of the nickname in TRILL switch settings?

- A. The nickname identifies the TRILL region and must match on every TRILL RBridge in the region.
- B. Administrators can use the nicknames to identify switches in CLI output.
- C. The nickname is the first factor for electing a root bridge
- D. TRILL RBridges use the nicknames as source and destination addresses in TRILL headers

Correct Answer: D

QUESTION 2

Which statement is correct about a Fibre Channel (FC) World Wide Name (WWN)?

- A. It is a hardware specific address for a LUN on a storage disk and can be used to direct FC frames to targets.
- B. It is a hardware specific address for an FC device and can be used to place the device in zones.
- C. It is assigned to an FC device based on its location and can be used to deliver FC frames
- D. It is assigned to an FC N-port as its switch joins the fabric and can be used to route FC frames

Correct Answer: B

QUESTION 3

What must be used when implementing the backbone multicast feature to isolate multicasts in the SPBM region?

- A. maximum of two Equal Cost Tree (ECT) algorithms
- B. single I-SID for all VLANs belonging to the same customer
- C. head-end replication for multicasts
- D. odd-numbered VLAN IDs for B-VLANs

Correct Answer: C

QUESTION 4

An HP Comware switch supports FCoE in Fibre Channel Forwarder (FCF) mode. A switch interface Ten1/0/1 connects to a server FCoE Converged Network Adapter (CNA). The CNA transmits normal data traffic, which is tagged for VLANs 4 and 8, and storage traffic for VSAN 2, which is associated with VLAN

20. What is a correct port type and VLAN configuration for Ten 1/0/1?



- A. a hybrid port that has PVID 1 and defines VLANs 4 and 8 as tagged
- B. a trunk port that has PVID 20 and permits VLANs 4, 8, and 20
- C. a hybrid port that has PVID 1, defines VLAN 20 as untagged, and defines VLANs 4 and 8 as tagged
- D. a trunk port that has PVID 1 and permits VLANs 4, 8, and 20

Correct Answer: D

QUESTION 5

When is it recommended to block VRRP hellos between routers in the same VRRP instance?

- A. when the VRRP master and VRRP backup router are part of the same IRF virtual device
- B. when providing two VRRP master routers to be deployed in different data centers
- C. when the VRRP master and VRRP backup router are part of a TRILL domain
- D. when the VRRP master and VRRP backup router are top of the rack (ToR) switches

Correct Answer: A

[Latest HP2-Z34 Dumps](#)

[HP2-Z34 PDF Dumps](#)

[HP2-Z34 VCE Dumps](#)