# HPE0-J80<sup>Q&As</sup>

HPE0-J80<sup>Q&As</sup>

## Delta - Architecting Multi-Site HPE Storage Solutions

## Pass HP HPE0-J80 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

**https://www.passapply.com/hpe0-j80.html**

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

## QUESTION 1

You are designing an iSCSI solution for a customer with one data center, who is investing in a second data center that will be ready in the near future. The networking infrastructure of the current data center is generally sufficient for use with an iSCSI storage solution, but it is from a different vendor. The new data center will be equipped with current HPE Networking switches.

A. For maximum performance, Jumbo Frames should be configured on the storage nodes only

B. Jumbo Frames are only required for low latency applications

C. Jumbo Frame sizes are not standardized across all switch vendors

D. Only switch ports must be configured to forward Jumbo Frames

Correct Answer: C

## QUESTION 2

You are planning a multi-site HPE StoreVirtual environment. The customer wants to use two VMware vSphere hosts at each datacenter.

Which StoreVirtual OS technology should be implemented as part of your plan to reduce network traffic between the sites?

A. I/O path preferencing

B. FOM quorum management

C. QoS

D. application-management snapshots

Correct Answer: D

## QUESTION 3

A customer has a multi-site environment and plans to consolidate file-and-block-level data. A proof of concept is arranged to familiarize the customer with HPE 3PAR StoreServ File Persona functionality.

Which statement is true when failing over file-level data between the arrays?

A. The Peer Persistence Arbitrator must register the file shares before a failover is initiated.

B. An automated failback is initiated once the primary storage system comes back online.

C. The clients must reconnect to NAS shares once failover is complete.

D. A second cluster IP must be configured as a DNS alias for the file shares running on the HPE 3PAR StoreServ.

Correct Answer: D

**QUESTION 4**

A customer\\'s business needs 247 uptime and highest data availability. In the past, the customer has experienced revenue loss from several outrages during firmware upgrade processes with non-HPE products due to temporary loss of access to disk enclosures. There is a need for 80 TB of Tier-0 storage. You propose cage availability in the new design, using an HPE 3PAR StoreServ 2-node system containing

80.92 TB cMLC SSD drivers.

When following HPE best practices, how many additional enclosures should be included in the system?

A. 0

B. 1

C. 2

D. 3

Correct Answer: D

**QUESTION 5**

You are demonstrating management of HPE 3PAR StoreServ arrays using HPE OneView. When you attempt to add an array, you cannot attach to it. What must you do to resolve this problem?

A. Reboot the HPE 3PAR StoreServ nodes, one at a time.

B. Restart the RESTful Application Program Interface (REST API).

C. Reboot the HPE OneView appliance.

D. Restart the Web Services Application Program Interface (WSAPI).

Correct Answer: D

[Latest HPE0-J80 Dumps](#)          [HPE0-J80 PDF Dumps](#)          [HPE0-J80 Braindumps](#)