



HPE0-V14^{Q&As}

Building HPE Hybrid IT Solutions

Pass HP HPE0-V14 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/hpe0-v14.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer needs a video archive repository initially starting at 30TB internal storage. The repository is expected to grow at 20% annually and should have a lifespan of 3 years. Which HPE ProLiant server solution meets the customer's requirements?

- A. HPE ProLiant DL560 Gen10 with LFF SAS drives
- B. HPE ProLiant DL380 Gen10 with LFF SAS drives
- C. HPE ProLiant ML110 with SFF SAS drives
- D. HPE ProLiant DL560 Gen9 with SFF SAS drives

Correct Answer: B

QUESTION 2

Which hardware and software components make up a Nimble dHCI infrastructure?

- A. HPE M-Series switch, HPE ProLiant DL servers, HPE Nimble, and VMware
- B. Aruba Switches, HPE Synergy, HPE Nimble, and VMware
- C. HPE M-Series switch, HPE ProLiant DL servers, HPE Nimble, and Hyper-V
- D. Aruba Switches, HPE Synergy, HPE Nimble, and Hyper-V

Correct Answer: A

Reference: <https://community.hpe.com/t5/HPE-Storage-Tech-Insiders/HPE-Nimble-Storage-dHCI-Technical-Overview/ba-p/7054163#.XnxfMW5RWQ4>

QUESTION 3

A customer reports that their new iSCSI MSA 2052 has failed. You find that the MSA is up and running, but the servers cannot mount their LUNs.

Which troubleshooting steps should you prioritize? (Choose two.)

- A. Use Smart Storage Administrator (SSA) to view the STATS report on the MSA
- B. Use NIC teaming utility to validate the iSCSI initiator configuration
- C. Use remote console to check the switch port configuration
- D. Use remote console to validate the WWNs on the MSA
- E. Use remote console to ensure correct MSA port configuration

Correct Answer: CE



QUESTION 4

What is used to identify a storage HBA port in a Fibre Channel SAN fabric?

- A. WWN
- B. MAC Address
- C. SCSI ID
- D. ION

Correct Answer: A

QUESTION 5

You are installing an HPE ProLiant server in a rack at a customer site. The customer's facility is in a high-voltage utility service area, and they want to be certain that the power supply is supported.

Which ProLiant feature addresses the customer's concern?

- A. ProLiant servers can be configured for 380 ?400V AC in low-line and high-line utility service areas.
- B. ProLiant servers support 240 V DC power supplies because components in a direct current line are less prone to failure.
- C. Rack-mountable HPE servers ship with 110 V DC power supplies because direct current is less expensive for a low-line utility service over short distances.
- D. ProLiant servers include auto-sensing power supplies with a power input range of 100-240 VAC, so they can be used globally.

Correct Answer: D

[HPE0-V14 PDF Dumps](#)

[HPE0-V14 VCE Dumps](#)

[HPE0-V14 Practice Test](#)