HPE6-A68^{Q&As}

Aruba Certified ClearPass Professional (ACCP) V6.7

Pass HP HPE6-A68 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/hpe6-a68.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official Exam Center

🛠 **Instant Download** After Purchase

🛠 **100% Money Back** Guarantee

🛠 **365 Days** Free Update

🛠 **800,000+** Satisfied Customers

QUESTION 1

Refer to the exhibit.

Based on the configuration of the Enforcement Profiles in the Onboard Authorization service shown, which Onboarding action will occur?

A. The device will be disconnected from the network after Onboarding so that an EAP-TLS authentication is not performed.

B. The device will be disconnected from and reconnected to the network after Onboarding is completed.

C. The device\\'s onboard authorization request will be denied.

D. The device will be disconnected after post-Onboarding EAP-TLS authentication, so a second EAP- TLS authentication is performed.

E. After logging in on the Onboard web login page, the device will be disconnected form and reconnected to the network before Onboard begins.

Correct Answer: B

QUESTION 2

Which IP address should be set as the DHCP relay on an Aruba Controller for device fingerprinting on ClearPass?

A. DHCP server IP

B. Active Directory IP

C. Switch IP

D. Microsoft NPS server IP

E. ClearPass server IP

Correct Answer: E

QUESTION 3

An organization implements dual SSID Onboarding. The administrator used the Onboard service template to create services for dual SSID Onboarding. Which statement accurately describes the outcome?

A. The Onboard Provisioning service is triggered when the user connects to the provisioning SSID to Onboard their device.

B. The Onboard Authorization service is triggered when the user connects to the secure SSID.

C. The Onboard Authorization service is triggered during the Onboarding process.

D. The device connects to the secure SSID for provisioning.

E. The Onboard Authorization service is never triggered.

Correct Answer: C

QUESTION 4

What is the purpose of RADIUS CoA (RFC 3576)?

A. to force the client to re-authenticate upon roaming to a new Controller

B. to apply firewall policies based on authentication credentials

C. to validate a host MAC address against a whitelist or a blacklist

D. to authenticate users or devices before granting them access to a network

E. to transmit messages to the NAD/NAS to modify a user\\'s session status

Correct Answer: E

CoA messages modify session authorization attributes such as data filters. References: https://tools.ietf.org/html/rfc3576

QUESTION 5

Which components can use Active Directory authorization attributes for the decision-making process? (Select two.)

A. Profiling policy

B. Certificate validation policy

C. Role Mapping policy

D. Enforcement policy

E. Posture policy

Correct Answer: CD

C: Role Mappings Page - Rules Editor Page Parameters

Parameter	Description
Type	The rules editor appears throughout the Policy Manager interface. It exposes different namespace dictionaries depending on context (Refer to Namespaces.) In the role mapping context, Policy Manager allows attributes from following namespaces: • Application • Application:ClearPass • Authentication • Authorization • Authorization:<authorization_source_instance> - Policy Manager shows each instance of the authorization source for which attributes have been configured to be fetched. (See Adding and Modifying Authentication Sources). Only those attributes that have been configured to be fetched are shown in the attributes drop down list. • Certificate • Connection • Date • Device • Endpoint • GuestUser • Host • LocalUser • Onboard • TACACS • RADIUS - All enabled RADIUS vendor dictionaries.
Name	Displays the drop-down list of attributes present in the selected namespace
Operator	Displays the drop-down list of context-appropriate (with respect to the attribute data type) operators. Operators have the obvious meaning; for stated definitions of operator meaning, refer to Operators.
Value	Depending on attribute data type this may be a free-form (one or many line) edit box, a drop-down list, or a time/date widget.

D: Enforcement Policy Attributes tab Parameters

Attribute	Description
Type:	Select the type of attributes from the drop-down list.
Host	See Host Namespaces
Authentication	See Authentication Namespaces
Connection	See Connection Namespaces
Application	See Application Namespace
• Radius:IETF • Radius:Cisco • Radius:Microsoft • Radius:Avenda • Radius:Aruba	See RADIUS Namespaces
Name	The options displayed for the **Name** attribute depend on the **Type** attribute that was selected.
Value	The options displayed for the **Value** attribute depend on the **Type** and **Name** attributes that were selected.

References:

http://www.arubanetworks.com/techdocs/ClearPass/Aruba_CPPMOnlineHelp/Content/CPPM_UserGuide/identity/RoleMappingPolicies.html http://www.arubanetworks.com/techdocs/ClearPass/Aruba_CPPMOnlineHelp/Content/

CPPM_UserGuide/PolicySim/PS_Enforcement_Policy.htm