



# JN0-1301<sup>Q&As</sup>

Data Center Design, Specialist (JNCDS-DC)

## Pass Juniper JN0-1301 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-1301.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





### QUESTION 1

When considering data center security, which component is often seen as unimportant but is really the first line of defense?

- A. guest access
- B. native VLAN configuration
- C. RBAC
- D. physical security

Correct Answer: A

---

### QUESTION 2

You have included in your data center design an SRX1500 chassis cluster. The RFP requires a documented upgrade process for the cluster that minimizes downtime. What satisfies this requirement in this scenario?

- A. an in-service software upgrade
- B. a topology-independent in-service software upgrade
- C. a manual device upgrade
- D. a nonstop software upgrade

Correct Answer: A

---

### QUESTION 3

A multi-tenant data center requires many thousands of VLANs for their customers. Additionally, they also need real-time data replication and server mobility to a remote backup site.

In this scenario, which solution should they choose?

- A. Virtual Chassis Fabric
- B. Clos IP fabric
- C. IBGP
- D. VXLAN

Correct Answer: D

---

### QUESTION 4



A customer is using EVPN to maximize their Data Center Interconnect and provide a stretched Layer 2 network to support VM mobility. What are two benefits in this scenario? (Choose two.)

- A. Load balancing is used across the WAN per flow
- B. Layer 2 MAC tables are populated using the control plane
- C. Load balancing is used across the WAN per packet
- D. Layer 2 MAC tables are populated using the data plane

Correct Answer: AB

---

#### QUESTION 5

You are implementing traffic prioritization in your IP fabric. You must ensure that traffic is handled correctly throughout the fabric.

In this scenario, which statement is correct?

- A. You should implement a BA classifier on all egress interfaces on the leaf devices.
- B. Rewrite rules must be applied on the spine devices for all leaf-facing interfaces.
- C. You should implement a BA classifier on all egress interfaces on the spine devices.
- D. Schedulers should be applied to all egress interfaces on your leaf and spine devices.

Correct Answer: D

[Latest JN0-1301 Dumps](#)

[JN0-1301 VCE Dumps](#)

[JN0-1301 Exam Questions](#)