



JN0-1331^{Q&As}

Security Design - Specialist (JNCDS-SEC)

Pass Juniper JN0-1331 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-1331.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

You are asked to include anti-malware features into an existing network design. Traffic from the infected machines must be moved to a quarantined VLAN.

Which product will provide this segregation?

- A. screens
- B. Sky ATP
- C. unified threat management
- D. Software Defined Secure Network

Correct Answer: B

Reference: https://www.juniper.net/documentation/en_US/release-independent/sky-atp/informationproducts/pathway-pages/sky-atp-admin-guide.pdf

QUESTION 2

What is the maximum number of SRX Series devices in a chassis cluster?

- A. 2
- B. 3
- C. 4
- D. 5

Correct Answer: A

Reference: <https://www.oreilly.com/library/view/juniper-srx-series/9781449339029/ch07.html>

QUESTION 3

Your company has 500 branch sites and the CIO is concerned about minimizing the potential impact of a VPN router being stolen from an enterprise branch site. You want the ability to quickly disable a stolen VPN router while minimizing administrative overhead.

Which solution accomplishes this task?

- A. Implement a certificate-based VPN using a public key infrastructure (PKI)
- B. Modify your IKE proposals to use Diffie-Hellman group 14 or higher
- C. Use firewall filters to block traffic from the stolen VPN router
- D. Rotate VPN pre-shared keys every month



Correct Answer: C

QUESTION 4

You are deploying Security Director with the logging and reporting functionality for VMs that use SSDs. You expect to have approximately 20,000 events per second of logging in your network.

In this scenario, what is the minimum number of logging and reporting devices that should be used?

- A. 2
- B. 4
- C. 1
- D. 3

Correct Answer: C

Reference: https://www.juniper.net/documentation/en_US/junos-space17.1/topics/task/multi-task/junosspace-sd-log-collector-installing.html

QUESTION 5

You have a site that has two Internet connections but no switch on the outside of the firewall. You want to use ISP-A over ISP-B during normal operations.

Which type of chassis cluster design would you propose to satisfy this requirement?

- A. Propose active/active cluster deployment with separate redundancy groups
- B. Propose active/passive cluster deployment with separate redundancy groups
- C. Propose active/active cluster deployment without separate redundancy groups
- D. Propose active/passive cluster deployment without separate redundancy groups

Correct Answer: A

Reference: https://www.juniper.net/documentation/en_US/release-independent/nce/topics/example/chassis-cluster-srx-active-active-configuring.html