JN0-1331^{Q&As}

Security Design - Specialist (JNCDS-SEC)

Pass Juniper JN0-1331 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.passapply.com/jn0-1331.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper Official Exam Center

QUESTION 1

Which two steps should be included in your security design process? (Choose two.)

A. Identify external attackers

B. Define safety requirements for the customer\\'s organization

C. Identify the firewall enforcement points

D. Define overall security policies

Correct Answer: CD

Reference: https://www.juniper.net/assets/us/en/local/pdf/whitepapers/2000591-en.pdf

QUESTION 2

You are asked to include anti-malware features into an existing network design. Traffic from the infected machines must be moved to a quarantined VLAN.

Which product will provide this segregation?

A. screens

B. Sky ATP

C. unified threat management

D. Software Defined Secure Network

Correct Answer: B

Reference: https://www.juniper.net/documentation/en_US/release-independent/sky-atp/informationproducts/pathway-pages/sky-atp-admin-guide.pdf

QUESTION 3

You are designing a solution to protect a service provider network against volumetric denial-of-service attacks. Your main concern is to protect the network devices. Which two solutions accomplish this task? (Choose two.)

A. next-generation firewall

B. screens

C. intrusion prevention system

D. BGP FlowSpec

Correct Answer: CD

Reference: https://www.juniper.net/documentation/en_US/day-one- books/DO_BGP_FLowspec.pdf

QUESTION 4

Which two features are used to stop IP spoofing in and out of your network? (Choose two.)

A. GeoIP

B. firewall filters

C. unicast reverse path forwarding

D. IPS

Correct Answer: CD

Reference: https://www.juniper.net/documentation/en_US/junos/topics/topic-map/security-attackerevasion-technique.html

QUESTION 5

You are designing an SDSN security solution for a new campus network. The network will consist of Juniper Networks Policy Enforcer, Juniper Networks switches, third-party switches, and SRX Series devices. The switches and the SRX Series devices will be used as security enforcement points. The design must be able to change the VLAN mapping of the switch port of a user that is already authenticated to the network in the event that the end user device becomes compromised.

Which component satisfies this requirement?

A. certificate server

B. RADIUS server

C. Security Director

D. DHCP server

Correct Answer: C