



JN0-1332^{Q&As}

Security Design Specialist (JNCDS-SEC)

Pass Juniper JN0-1332 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-1332.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

You will be managing 1000 SRX Series devices. Each SRX Series device requires basic source NAT to access the Internet.

Which product should you use to manage these NAT rules on the SRX Series devices?

- A. Security Director
- B. CSO
- C. Contrail
- D. JSA

Correct Answer: A

QUESTION 2

You must allow applications to connect to external servers. The session has embedded IP address information to enable the remote system to establish a return session.

In your design, which function should be implemented?

- A. source NAT
- B. application layer gateway
- C. destination NAT
- D. HTTP redirect

Correct Answer: A

QUESTION 3

You are designing a DDoS solution for an ISP using BGP FlowSpec. You want to ensure that BGP FlowSpec does not overwhelm the ISP's edge routers.

Which two requirements should be included in your design? (Choose two.)

- A. Specify a maximum number BGP FlowSpec prefixes per neighbor
- B. Implement a route policy to limit advertised routes to /24 subnets
- C. Implement a route policy to limit advertised routes to any public IP space
- D. Specify a maximum number of BGP FlowSpec prefixes per device

Correct Answer: CD



Reference: https://www.juniper.net/documentation/en_US/day-one-books/DO_BGP_FlowSpec.pdf

QUESTION 4

In a data center, what are two characteristics of access tier VLAN termination on the aggregation tier? (Choose two.)

- A. Multiple VLANs can be part of one security zone
- B. A security zone is limited to a single VLAN
- C. Inter-VLAN traffic within a zone can bypass firewall services
- D. Inter-VLAN traffic is secured through firewall services

Correct Answer: AD

QUESTION 5

You are designing an Internet security gateway (ISG) for your company and are considering a centralized versus a distributed model for ISGs.

Which two statements are correct in this scenario? (Choose two.)

- A. Distributed ISGs typically have less latency compared to centralized ISGs
- B. Distributed ISGs reduce bandwidth for end users
- C. Distributed ISGs typically require extra bandwidth for management
- D. Distributed ISGs are harder to manage compared to centralized ISGs

Correct Answer: AD

[JN0-1332 PDF Dumps](#)

[JN0-1332 Practice Test](#)

[JN0-1332 Exam Questions](#)