



# JN0-361<sup>Q&As</sup>

Service Provider Routing and Switching, Specialist Exam

## Pass Juniper JN0-361 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-361.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper  
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





### QUESTION 1

You have been asked to verify the state of an LDP-signaled Layer 2 circuit. Which two commands would you use to verify the state of the connection? (Choose two.)

- A. show mpls lsp
- B. show l2circuit connections
- C. show l2circuit statistics
- D. show ldp database

Correct Answer: BD

---

### QUESTION 2

Click the Exhibit button.

```
[edit]
user@host# show protocols ospf3
area 30.35.16.25 {
    interface all;
}
```

Which statement is true regarding the output shown in the exhibit?

- A. The configuration supports IPv6 multicast routes.
- B. The configuration supports IPv6 unicast routes.
- C. The configuration supports IPv4 unicast routes.
- D. The configuration supports IPv4 multicast routes.

Correct Answer: B

By default, OSPFv3 supports unicast IPv6 routes, but you can configure OSPFv3 to support multiple address families. To support an address family other than unicast IPv6, you configure a realm that allows

OSPFv3 to advertise IPv4 unicast, IPv4 multicast, or IPv6 multicast routes.

Example of a configuration which support both ipv4 and ipv6 prefixes:

```
user@host# show protocols ospf3
```

```
realm ipv4-unicast {
```

```
area 0.0.0.0 {
```

```
interface fe-0/1/0.0;
```



```
}  
  
}  
  
area 0.0.0.0 {  
  
interface fe-0/1/0.0;  
  
}
```

References: [http://www.juniper.net/documentation/en\\_US/junos15.1/topics/topic-map/ospfv3-multipleaddress-families.html](http://www.juniper.net/documentation/en_US/junos15.1/topics/topic-map/ospfv3-multipleaddress-families.html)

---

### QUESTION 3

Which statement is correct about the inet.3 routing table?

- A. MPLS creates a copy of the mpls.0 table and stores it in the inet.3 routing table.
- B. The inet.3 routing table is used by transit routers to identify label values.
- C. BGP can use the inet.3 routing table to resolve next hops.
- D. MPLS uses the inet.3 routing table to assign labels.

Correct Answer: C

---

### QUESTION 4

Which two Layer 2 protocols are supported on MX Series devices? (Choose two.)

- A. BGP
- B. RIP
- C. RSTP
- D. MSTP

Correct Answer: CD

---

### QUESTION 5

Which type of BGP message is used to perform a soft clearing of a BGP session?

- A. refresh
- B. update
- C. notification



D. open

Correct Answer: A

A refresh message is used to perform a soft clearing of a BGP session. Normally a BGP speaker cannot be made to readvertise routes that have already been sent and acknowledged. The route refresh message supports soft clearing of BGP sessions by allowing a peer to readvertise routes that have already been sent.

[Latest JN0-361 Dumps](#)

[JN0-361 PDF Dumps](#)

[JN0-361 Braindumps](#)