



JN0-451^{Q&As}

Mist AI - Specialist (JNCIS-MistAI)

Pass Juniper JN0-451 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-451.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Site A is configured with a WLAN and a policy. The administrator creates a configuration template at the organization level with additional policies for the same WLAN and mentions Site A in this template. In this scenario, which statement is correct?

- A. The policy that is created in the config template at the organization level will execute first.
- B. The policy created at the organization level can be applied to a site group, not to an individual site.
- C. The policy that is created at the site level will execute first.
- D. There is no option to mention the site in the config template at the organization level.

Correct Answer: A

Reference: [https://www.mist.com/documentation/create-1st-wlan-using-configuration- templates/](https://www.mist.com/documentation/create-1st-wlan-using-configuration-templates/)

QUESTION 2

Which two statements correctly describe an extended service set (ESS)? (Choose two.)

- A. Each BSS within the ESS share a common BSSID.
- B. Each BSS within the ESS has its own unique BSSID.
- C. The SSID is common across all BSSs within the ESS.
- D. The SSID is unique across all BSSs within the ESS.

Correct Answer: AC

QUESTION 3

Mist WLAN objects are configurable at which two levels? (Choose two.)

- A. site group
- B. organization
- C. site
- D. access point

Correct Answer: CD

QUESTION 4

You receive a Marvis Actions alert informing you that there is a non-compliant AP at one of your sites. What should you



do to correct the problem?

- A. Request an RMA.
- B. Disconnect the Rogue AP from your Ethernet switch.
- C. Replace the AP with the correct hardware model.
- D. Install the correct version of firmware on the AP.

Correct Answer: D

Reference: <https://www.mist.com/documentation/what-is-marvis-actions/>

QUESTION 5

When does a Mist AP actually begin transmitting BLE?

- A. When it is claimed and placed on a site.
- B. When it is placed on a floor plan.
- C. When BLE is enabled at the Organization level.
- D. When BLE is enabled for the AP.

Correct Answer: D

Reference: <https://www.mist.com/documentation/ble-mac-randomization/>

[Latest JN0-451 Dumps](#)

[JN0-451 VCE Dumps](#)

[JN0-451 Exam Questions](#)