



JN0-681^{Q&As}

New Data Center, Professional

Pass Juniper JN0-681 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-681.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





QUESTION 1

When using EBGp as the underlay protocol for your IP fabric architecture, which two statements are true? (Choose two.)

- A. Spine nodes only peer to leaf nodes.
- B. Leaf nodes peer to both spine and leaf nodes.
- C. Leaf nodes only peer to spine nodes.
- D. Spine nodes peer to both leaf and spine nodes.

Correct Answer: AC

QUESTION 2

Which two statements describe EVPN-based VXLAN implementations? (Choose two.)

- A. The movement of a virtual host requires a manual reconfiguration of the VTEP.
- B. The movement of a virtual host results in the dynamic remapping of the VTEP.
- C. MAC addresses are learned using multicast flooding.
- D. MAC addresses are propagated using BGP updates.

Correct Answer: BD

QUESTION 3

What happens when a packet is encapsulated by a VXLAN before being placed in the overlay?

- A. The QoS markings are placed in the VXLAN header.
- B. The VLAN-ID is placed in the VXLAN header.
- C. A VNI that maps to the VLAN-ID is placed in the VXLAN header.
- D. The TTL is decremented by two and placed in the VXLAN header.

Correct Answer: C

QUESTION 4

You want to configure redundant Layer 3 gateways.

In this scenario, which two Juniper best practices would accomplish this task? (Choose two.)



- A. configuring both IRB interfaces manually with the same MAC address.
- B. allowing Junos to dynamically create the virtual IP address of the IRB interface.
- C. configuring both IRB interfaces manually with the same IP address.
- D. allowing Junos to dynamically create the virtual MAC address of the IRB interface.

Correct Answer: CD

QUESTION 5

Which two statements define the use of route targets and route distinguishers in an EVPN? (Choose two.)

- A. Route targets ensure that routes from different clients remain unique within the data center domain.
- B. Route targets identify the VRF into which the route should be placed.
- C. Route distinguishers ensure that routes from different clients remain unique within the data center domain.
- D. Route distinguishers identify the VRF into which the route should be placed.

Correct Answer: BC

[JN0-681 PDF Dumps](#)

[JN0-681 Exam Questions](#)

[JN0-681 Braindumps](#)