



JN0-682^{Q&As}

Data Center Professional (JNCIP-DC)

Pass Juniper JN0-682 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.passapply.com/jn0-682.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Juniper
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

The configuration shown in the exhibit is intended to set up assisted replication but will not commit. Which action will create a valid configuration in this situation?

```
Exhibit
192.168.100.1;
  vxlan-encapsulation-source-ip ingress-replication-ip;
}
extended-vni-list all;
}
(master:0)(edit)
user@spine1# show interfaces lo0
unit 0 {
  family inet {
    address 192.168.100.1/32;
    address 192.168.100.51/32;
  }
}
unit 1 {
  family inet {
    address 192.168.100.101/32;
  }
}
```

- A. Change the 10.0 address to 192.168.100.1 primary.
- B. Change the replicator inet address to 192.168.100.101.
- C. Delete replicator inet 192.168.100.1.
- D. Change the replicator inet address to 192.168.100. 51.

Correct Answer: B

QUESTION 2

What are three advantages of using MPLS for data center interconnects? (Choose two.)

- A. Dedicated MPLS backbones for Layer 1 and Layer 3 DCIs
- B. Any to any connectivity
- C. Dedicated connections between customer sites
- D. Sub 50 ms failover times
- E. Traffic engineering

Correct Answer: ADE



QUESTION 3

You are building an IP fabric underlay network for your new data center. You must ensure that you have predictable load-balancing behavior throughout your network. According to Juniper Networks, what are two best practices that should be followed in this scenario? (Choose two.)

- A. All leaf devices must be identical to the spine device models including the same installed line cards.
- B. All spine devices should be identical models including the same installed line cards.
- C. Every leaf device should have an identical uplink to every other leaf device.
- D. Every leaf device should have an identical uplink to every spine device.

Correct Answer: BD

QUESTION 4

You are creating a new EVPN and are asked to selectively accept certain MAC advertisement routers from your EVPN peers using VXLAN Encapsulation.

Which statements is correct in this scenario?

- A. You can use VRF policies and route distinguisher values to filter out unwanted routes.
- B. You can use VBRF import policies and community values to filter out unwanted routes.
- C. You can use MAC filtering to filter out unwanted routes.
- D. You can use firewall filters to filters out unwanted routes

Correct Answer: B

QUESTION 5

After configuring an IP fabric using EBGP as you protocol, you notice that not all of the routers are showing up in the routing tables. You have verified that all adjacencies have formed, and place and configured properly. In this scenario, which statement is true?

- A. The routers have not been configured with the multipath multiple-as parameter.
- B. The routers have not been configured using the bfd-1 Liveness-detection parameter.
- C. The routers have not been configured using the multihop parameter.
- D. The routers have not been configured using the add-path parameter

Correct Answer: A



VCE & PDF

PassApply.com

<https://www.passapply.com/jn0-682.html>

2024 Latest passapply JN0-682 PDF and VCE dumps Download

[Latest JN0-682 Dumps](#)

[JN0-682 PDF Dumps](#)

[JN0-682 Study Guide](#)